

REVOLT ADVANCED SL 1



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Tempest Purple
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
GAFFEL	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm
GRIPS	Stratus Lite 3.0
STYRSTEM	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SETEPINNE	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SADEL	Giant Grit SLR
DRIVVERK	
GIRHENDLER	SRAM Force XPLR AXS E1, 1x13
BAKGIR	SRAM Force XPLR AXS E1
BREMSE	SRAM Force AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
BREMSEHENDLER	SRAM Force E1 hydraulic
KASSETT	SRAM Force E1, 13-speed, 10x46
KJEDE	SRAM Force E1
KRANK	SRAM Force XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NAV	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
EIKE	Aero Bladed Carbon Spoke
DEKK	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	700x53mm
MAX CHAINRING SIZE	54t

GEOMETRI

RAMME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	75,0°	74,5°	74,5°	74,0°	74,0°	74,0°
Top Tube Length (mm)	530	540	550	565	580	590
Head Tube Length (mm)	90	100	120	135	155	180
Head Tube Angle	70,5°	71,0°	71,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78	74	71	67	67	67
Wheelbase (mm)	1026	1027	1033	1039	1055	1066
Chain Stay Length (mm)	433	433	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80	80	80
Stack (mm)	525	536	557	573	592	616
Reach (mm)	389	391	395	401	410	413
Stand Over Height (mm)	726	743	762	779	798	818
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	70	80	90	100	100	110
Crank Length (mm)	165	165	170	170	172,5	172,5
Wheel Size	700C	700C	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.