

REVOLT ADVANCED SL 2

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Deep Lagoon
CUADRO	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
TIJERA	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTES	
MANUBRIO	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
GRIPS	Stratus Lite 3.0
POTENCIA	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
POSTE DE ASIENTO	Giant Contact SLR XR D-Fuse, composite, 20mm offset
ASIENTO	Giant Grit SL
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Rival AXS E1, 1x13
CAMBIO TRASERO	SRAM Rival XPLR AXS E1
FRENOS	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	SRAM Rival E1 hydraulic
CASSETTE	SRAM Rival E1, 13-speed, 10x46
CADENA	SRAM Rival E1
MULTIPLICACIÓN	SRAM Rival XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
MAZAS	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
RAYOS	Aero Bladed Carbon Spoke
NEUMÁTICOS	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	53mm max tire size
MAX CHAINRING SIZE	54t max chainring size

Precio: \$122,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud de la Base del Poste de Asiento (mm)	430	450	470	490	510	530
Ángulo de la Base del Poste de Asiento	75.0°	74.5°	74.5°	74.0°	74.0°	74.0°
Longitud del Tubo Superior (mm)	530	540	550	565	580	590
Longitud del Telescopio (mm)	90	100	120	135	155	180
Ángulo del Telescopio	70.5°	71.0°	71.5°	72.0°	72.0°	72.0°
Rake (mm)	50	50	50	50	50	50
Trail (mm)	78	74	71	67	67	67
Distancia entre Ejes (mm)	1026	1027	1033	1039	1055	1066
Longitud de Vaina Inferior (mm)	433	433	433	433	433	433
Caída del Eje de Centro (mm)	80	80	80	80	80	80
Stack (mm)	525	536	557	573	592	616
Reach (mm)	389	391	395	401	410	413
Altura del Tubo Superior al Suelo (mm)	726	743	762	779	798	818
Ancho del Manubrio (mm)	380	380	400	400	420	420
Longitud de la Potencia (mm)	70	80	90	100	100	110
Longitud de la Biela (mm)	165	165	170	170	172.5	172.5
Tamaño de las Ruedas	700C	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.