

REVOLT ADVANCED SL 2



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, M/L, L, XL
VÄRIT	Deep Lagoon
RUNKO	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
HAARUKKA	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMONENTIT	
OHJAUSTANKO	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
GRIPIT	Stratus Lite 3.0
OHJAINKANNATIN	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SATULATOLPPA	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SÄTULÄ	Giant Grit SL
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Rival AXS E1, 1x13
TAKAVAIHTAJA	SRAM Rival XPLR AXS E1
JARRUT	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
JARRUKAHVAT	SRAM Rival E1 hydraulic
RATASPAKKA	SRAM Rival E1, 13-speed, 10x46
KETJUT	SRAM Rival E1
KAMPISARJA	SRAM Rival XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NAVAT	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
PINNAT	Aero Bladed Carbon Spoke
RENKAAT	CADEX GXR, 700x45c, tubeless
LISÄTIEDOT	tubeless prepared, computer mount, chain guide
RAJOITTEET	
MAX RENGASVARA	53mm max tire size
MAX KETJUN KOKO	54t max chainring size

Suositusinta: 6 909,00 €

GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	450	470	490	510	530
Satulaputken kulma	74,5°	74,5°	74,0°	74,0°	74,0°
Vaakaputken pituus (mm)	540	550	565	580	590
Emäputken pituus (mm)	100	120	135	155	180
Emäputken kulma	71,0°	71,5°	72,0°	72,0°	72,0°
Haarukan offset (mm)	50	50	50	50	50
Trail-mitta (mm)	74	71	67	67	67
Akseliväli (mm)	1027	1033	1039	1055	1066
Takahaarukan alaputken pituus (mm)	433	433	433	433	433
Keskiön pudotus (mm)	80	80	80	80	80
Stack-mitta (mm)	536	557	573	592	616
Reach-mitta (mm)	391	395	401	410	413
Standover-mitta (mm)	743	762	779	798	818
Ohjaustangon leveys (mm)	380	400	400	420	420
Ohjainkannattimen pituus (mm)	80	90	100	100	110
Kammen pituus (mm)	165	170	170	172,5	172,5
Rengaskoko	700C	700C	700C	700C	700C

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.