

REVOLT ADVANCED SL 2



TECHNIQUES

CADRE	
TAILLES	XS, S, M, ML, L, XL
COLORIS	Deep Lagoon
CADRE	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FOURCHE	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPOSANTS	
CINTRE	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
TIGE DE SELLE	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SELLE	Giant Grit SL
DÉRAILLEUR	
MANETTES	SRAM Rival AXS E1, 1x13
DÉRAILLEUR ARRIÈRE	SRAM Rival XPLR AXS E1
FREINS	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
LEVIER DE FREIN	SRAM Rival E1 hydraulic
CASSETTE	SRAM Rival E1, 13-speed, 10x46
CHAÎNE	SRAM Rival E1
PÉDALIER	SRAM Rival XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
MOYEURS	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
RAYONS	Aero Bladed Carbon Spoke
PNEUS	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	53mm max tire size
TAILLE MAXIMALE DU PLATEAU	54t max chainring size

Prix Public Conseillé: 6 600,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	430	450	470	490	510	530
Angle de tube de selle	75,0°	74,5°	74,5°	74,0°	74,0°	74,0°
Longueur du tube supérieur (mm)	530	540	550	565	580	590
Longueur du tube de direction (mm)	90	100	120	135	155	180
Angle du tube de direction	70,5°	71,0°	71,5°	72,0°	72,0°	72,0°
Déport de fourche (mm)	50	50	50	50	50	50
Trail (mm)	78	74	71	67	67	67
Empattement (mm)	1026	1027	1033	1039	1055	1066
Longueur des bases (mm)	433	433	433	433	433	433
Drop du boîtier de pédalier (mm)	80	80	80	80	80	80
Stack (mm)	525	536	557	573	592	616
Reach (mm)	389	391	395	401	410	413
Hauteur en statique (mm)	726	743	762	779	798	818
Largeur de cintre (mm)	380	380	400	400	420	420
Longueur de potence (mm)	70	80	90	100	100	110
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5
Diamètre des roues	700C	700C	700C	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).