

REVOLT ADVANCED SL 2



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Deep Lagoon
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
VOORVORK	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
ZADELLEN	Giant Contact SLR XR D-Fuse, composite, 20mm offset
ZADEL	Giant Grit SL
AFMONTAGE	
SHIFTERS	SRAM Rival AXS E1, 1x13
ACHTTERDERAILLEUR	SRAM Rival XPLR AXS E1
REMMEN	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Rival E1 hydraulic
CASSETTE	SRAM Rival E1, 13-speed, 10x46
AANDRIJVING	SRAM Rival E1
CRANKSET	SRAM Rival XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NAVEN	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
SPAKEN	Aero Bladed Carbon Spoke
BANDEN	CADEX GXR, 700x45c, tubeless
EXTRA'S	tubeless prepared, computer mount, chain guide
LIMITS	
MAXIMALE BANDENVRIJHEID	53mm max tire size
MAXIMALE KETTINGBLADMAAT	54t max chainring size

Adviesprijs: € 6.499,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	450	470	490	510	530
Zitbuis Hoek	74,5°	74,5°	74,0°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	540	550	565	580	590
Balhoofdbuis Lengte (mm)	100	120	135	155	180
Balhoofdbuis Hoek	71,0°	71,5°	72,0°	72,0°	72,0°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	74	71	67	67	67
Wielbasis (mm)	1027	1033	1039	1055	1066
Liggende achtersvork lengte (mm)	433	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80	80
Stack (mm)	536	557	573	592	616
Reach (mm)	391	395	401	410	413
Stand Over Height (mm)	743	762	779	798	818
Stuur breedte (mm)	380	400	400	420	420
Stuurpen Lengte (mm)	80	90	100	100	110
Cranklengte (mm)	165	170	170	172,5	172,5
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.