

REVOLT ADVANCED SL FRAMESET

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Superspeed Teal
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORGAFFEL	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
FREMPIND	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SADELPIND	Giant Contact SLR XR D-Fuse, composite, 20mm offset

HJUL	
EKSTRA	Computer mount, chain guide
GRÆNSER	
MAX DÆKSTØRRELSE	700x53mm
MAX KLINGE STØRRELSE	54t

Pris: 31.799,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørs længde (mm)	450	470	490	510	530
Sadelrørsvinkel	74,5°	74,5°	74,0°	74,0°	74,0°
Overrørs længde (mm)	540	550	565	580	590
Kronrørs længde (mm)	100	120	135	155	180
Kronrørsvinkel	71,0°	71,5°	72,0°	72,0°	72,0°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	74	71	67	67	67
Akselafstand (mm)	1027	1033	1039	1055	1066
Kædestags længde (mm)	433	433	433	433	433
Krankboks drop (mm)	80	80	80	80	80
Stack (mm)	536	557	573	592	616
Reach (mm)	391	395	401	410	413
Skridthøjde (mm)	743	762	779	798	818
Styrbredde (mm)	380	400	400	420	420
Frempindslængde (mm)	80	90	100	100	110
Pedalarmslængde (mm)	165	170	170	172,5	172,5
Hjulstørrelse	700C	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.