

# REVOLT ADVANCED SL FRAMESET



## SPECS

FRAME	
<b>SIZES</b>	S, M, M/L, L, XL
<b>COLOURS</b>	Superspeed Teal
<b>FRAME</b>	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
<b>FORK</b>	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XR Integrated XS:70x38/42cm, S:80x38/42cm, M:90x40/44cm, M/L:100x40/44cm, L:100x40/44cm, XL:110x42/46cm
<b>STEM</b>	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
<b>SEATPOST</b>	Giant Contact SLR XR D-Fuse, composite, 20mm offset

WHEELS	
<b>EXTRAS</b>	Computer mount, chain guide
LIMITS	
<b>MAX TYRE CLEARANCE</b>	53mm
<b>MAX CHAINRING SIZE</b>	54t

**Price: \$5,999.00**

## GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	450	470	490	510	530
Seat Tube Angle	74.5°	74.5°	74.0°	74.0°	74.0°
Top Tube Length (mm)	540	550	565	580	590
Head Tube Length (mm)	100	120	135	155	180
Head Tube Angle	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	74	71	67	67	67
Wheelbase (mm)	1027	1033	1039	1055	1066
Chain Stay Length (mm)	433	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80	80
Stack (mm)	536	557	573	592	616
Reach (mm)	391	395	401	410	413
Stand Over Height (mm)	743	762	779	798	818
Stem Length (mm)	80	90	100	100	110
Crank Length (mm)	165	170	170	172.5	172.5
Wheel Size	700C	700C	700C	700C	700C

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.*