

# REVOLT ADVANCED SL FRAMESET



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Superspeed Teal
<b>FRAME</b>	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
<b>FORK</b>	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
<b>STEM</b>	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
<b>SEATPOST</b>	Giant Contact SLR XR D-Fuse, composite, 20mm offset

WHEELS	
<b>EXTRAS</b>	Computer mount, chain guide
LIMITS	
<b>MAX TIRE CLEARANCE</b>	700x53mm
<b>MAX CHAINRING SIZE</b>	54t

**Suggested Retail Price (CDN): \$5,899.00**

## FRAME GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°	74.0°	74.0°
Top Tube Length (mm)	530	540	550	565	580	590
Head Tube Length (mm)	90	100	120	135	155	180
Head Tube Angle	70.5°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78	74	71	67	67	67
Wheelbase (mm)	1026	1027	1033	1039	1055	1066
Chain Stay Length (mm)	433	433	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80	80	80
Stack (mm)	525	536	557	573	592	616
Reach (mm)	389	391	395	401	410	413
Stand Over Height (mm)	726	743	762	779	798	818
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	70	80	90	100	100	110
Crank Length (mm)	165	165	170	170	172.5	172.5
Wheel Size	700C	700C	700C	700C	700C	700C

*All prices and specifications are subject to change without notice.*