

REVOLT ADVANCED SL FRAMESET

GIANT



SPECS

| FRAME      |                                                                                                               |
|------------|---------------------------------------------------------------------------------------------------------------|
| SIZES      | XS, S, M, M/L, L, XL                                                                                          |
| COLOURS    | Superspeed Teal                                                                                               |
| FRAME      | Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout                                            |
| FORK       | Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc                  |
| COMPONENTS |                                                                                                               |
| HANDLEBAR  | Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm |
| STEM       | Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110                                   |
| SEATPOST   | Giant Contact SLR XR D-Fuse, composite, 20mm offset                                                           |

| WHEELS             |                             |
|--------------------|-----------------------------|
| EXTRAS             | Computer mount, chain guide |
| LIMITS             |                             |
| MAX TIRE CLEARANCE | 700x53mm                    |
| MAX CHAINRING SIZE | 54t                         |

Price: €4,649.00

GEOMETRY

| FRAME                    | XS    | S     | M     | ML    | L     | XL    |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 430   | 450   | 470   | 490   | 510   | 530   |
| Seat Tube Angle          | 75.0° | 74.5° | 74.5° | 74.0° | 74.0° | 74.0° |
| Top Tube Length (mm)     | 530   | 540   | 550   | 565   | 580   | 590   |
| Head Tube Length (mm)    | 90    | 100   | 120   | 135   | 155   | 180   |
| Head Tube Angle          | 70.5° | 71.0° | 71.5° | 72.0° | 72.0° | 72.0° |
| Fork Rake (mm)           | 50    | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)               | 78    | 74    | 71    | 67    | 67    | 67    |
| Wheelbase (mm)           | 1026  | 1027  | 1033  | 1039  | 1055  | 1066  |
| Chain Stay Length (mm)   | 433   | 433   | 433   | 433   | 433   | 433   |
| Bottom Bracket Drop (mm) | 80    | 80    | 80    | 80    | 80    | 80    |
| Stack (mm)               | 525   | 536   | 557   | 573   | 592   | 616   |
| Reach (mm)               | 389   | 391   | 395   | 401   | 410   | 413   |
| Stand Over Height (mm)   | 726   | 743   | 762   | 779   | 798   | 818   |
| Handlebar Width (mm)     | 380   | 380   | 400   | 400   | 420   | 420   |
| Stem Length (mm)         | 70    | 80    | 90    | 100   | 100   | 110   |
| Crank Length (mm)        | 165   | 165   | 170   | 170   | 172.5 | 172.5 |
| Wheel Size               | 700C  | 700C  | 700C  | 700C  | 700C  | 700C  |

All specifications listed are subject to change without notice.