

REVOLT ADVANCED SL FRAMESET

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Superspeed Teal
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORK	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
STEM	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SEATPOST	Giant Contact SLR XR D-Fuse, composite, 20mm offset

WHEELS	
EXTRAS	Computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	700x53mm
MAX CHAINRING SIZE	54t

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (inch)	16.9	17.7	18.5	19.3	20.1	20.9
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°	74.0°	74.0°
Top Tube Length (inch)	20.9	21.3	21.7	22.2	22.8	23.2
Head Tube Length (inch)	3.5	3.9	4.7	5.3	6.1	7.1
Head Tube Angle	70.5°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (inch)	2	2	2	2	2	2
Trail (inch)	3.1	2.9	2.8	2.6	2.6	2.6
Wheelbase (inch)	40.4	40.4	40.7	40.9	41.5	42
Chain Stay Length (inch)	17	17	17	17	17	17
Bottom Bracket Drop (inch)	3.1	3.1	3.1	3.1	3.1	3.1
Stack (inch)	20.7	21.1	21.9	22.6	23.3	24.3
Reach (inch)	15.3	15.4	15.6	15.8	16.1	16.3
Stand Over Height (inch)	28.6	29.3	30	30.7	31.4	32.2
Handlebar Width (inch)	15	15	15.7	15.7	16.5	16.5
Stem Length (inch)	2.8	3.1	3.5	3.9	3.9	4.3
Crank Length (inch)	6.5	6.5	6.7	6.7	6.8	6.8
Wheel Size	700C	700C	700C	700C	700C	700C

**All specifications and prices listed are subject to change without notice.
Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*