

REVOLT ADVANCED SL FRAMESET

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, M/L, L, XL
VÄRIT	Superspeed Teal
RUNKO	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
HAARUKKA	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMONENTIT	
OHJAUSTANKO	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
OHJAINKANNATIN	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SATULATOLPPA	Giant Contact SLR XR D-Fuse, composite, 20mm offset

RENKAAT	
LISÄTIEDOT	Computer mount, chain guide
RAJOITTEET	
MAX RENGASVARA	700x53mm
MAX KETJUN KOKO	54t

Suositusuhinta: 4 299,00 €

GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	450	470	490	510	530
Satulaputken kulma	74,5°	74,5°	74,0°	74,0°	74,0°
Vaakaputken pituus (mm)	540	550	565	580	590
Emäputken pituus (mm)	100	120	135	155	180
Emäputken kulma	71,0°	71,5°	72,0°	72,0°	72,0°
Haarukan offset (mm)	50	50	50	50	50
Trail-mitta (mm)	74	71	67	67	67
Akseliväli (mm)	1027	1033	1039	1055	1066
Takahaarukan alaputken pituus (mm)	433	433	433	433	433
Keskiön pudotus (mm)	80	80	80	80	80
Stack-mitta (mm)	536	557	573	592	616
Reach-mitta (mm)	391	395	401	410	413
Standover-mitta (mm)	743	762	779	798	818
Ohjaustangon leveys (mm)	380	400	400	420	420
Ohjainkannattimen pituus (mm)	80	90	100	100	110
Kammen pituus (mm)	165	170	170	172,5	172,5
Rengaskoko	700C	700C	700C	700C	700C

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.