

REVOLT ADVANCED SL FRAMESET



SPECS

RAM	
STORLEKAR	S, M, M/L, L, XL
FÄRGER	Superspeed Teal
RAM	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
GAFFEL	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
STAM	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SADELSTOLPE	Giant Contact SLR XR D-Fuse, composite, 20mm offset

HJUL	
EXTRAFUNKTIONER	Computer mount, chain guide
GRÄNSER	
MAX DÄCKAVSTÅND	700x53mm
MAX KEDJERINGSTORLEK	54t

Price: 47 990,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	450	470	490	510	530
Vinkel sadelrör	74,5°	74,5°	74,0°	74,0°	74,0°
Topprörets längd (mm)	540	550	565	580	590
Styrhuvud Längd (mm)	100	120	135	155	180
Vinkel styrhuvud	71,0°	71,5°	72,0°	72,0°	72,0°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	74	71	67	67	67
Hjulbas (mm)	1027	1033	1039	1055	1066
Kedjestagslängd (mm)	433	433	433	433	433
Nedre fäste Drop (mm)	80	80	80	80	80
Stack (mm)	536	557	573	592	616
Reach (mm)	391	395	401	410	413
Stå över höjden (mm)	743	762	779	798	818
Styrets bredd (mm)	380	400	400	420	420
Stamlängd (mm)	80	90	100	100	110
Vevlängd (mm)	165	170	170	172,5	172,5
Hjulstorlek	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.