

REVOLT E+ 2



SPECS

HYBRID CYCLING TECHNOLOGY

| | |
|-------------------|---|
| MOTOR | SyncDrive Sport2, 75Nm, powered by Yamaha |
| CONTROLLER | RideControl Ergo 2 remote, 5 power levels plus Smart Assist auto mode |
| DISPLAY | RideControl GO, frame integrated LED console optional ANT+ wireless display compatible |
| BATTERY | EnergyPak 400Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production EnergyPak Plus 200Wh range extender compatible |
| CHARGER | EnergyPak 4A smart charger, 60% in 1:45h |

FRAME

| | |
|----------------|--|
| SIZES | XS, S, M, M/L |
| COLOURS | Rainbow White |
| FRAME | ALUXX SL-grade aluminum, 1.125" - 1.25" head tube, 12x142 thru-axle, KSA18 kickstand mount |
| FORK | Advanced-grade composite, 12x100mm thru-axle |
| SHOCK | N/A |

COMPONENTS

| | |
|------------------|-------------------------------------|
| HANDLEBAR | Giant Contact XR D-Fuse, 31.8mm |
| GRIPS | Cork tape with gel |
| STEM | Giant Contact AeroLight, -10 degree |
| SEATPOST | Giant D-Fuse, alloy, 14mm offset |
| SADDLE | Giant Approach |
| PEDALS | N/A |

DRIVETRAIN

| | |
|------------------------|---|
| SHIFTERS | Shimano GRX RD-RX812 |
| REAR DERAILLEUR | Shimano GRX RD-RX812 |
| BRAKES | Shimano GRX RX400 hydraulic Shimano RT65 [F]180mm, [R]160mm |
| BRAKE LEVERS | Shimano GRX RX600 |
| CASSETTE | Shimano Deore, 11-speed, 11-42 |
| CHAIN | KMC e.11 Sport, EcoProteq, e-bike optimized |
| CRANKSET | FSA E-crank alloy, SRAM X-SYNC chain ring 46t, 107BCD |
| BOTTOM BRACKET | N/A |

WHEELS

| | |
|---------------|--|
| RIMS | Giant eX 2 Disc wheelset, alloy, tubeless ready, 22mm IW, 24mm H |
| HUBS | Giant eTracker, [F] 100x12mm thru-axle, [R] 142x12mm thru-axle |
| SPOKES | Sapim [F] Race, [R] E-Lite, e-bike optimized |
| TIRES | Giant Gavia Fondo AR 2, tubeless, 700x40c, 60 TPI, wire bead |
| EXTRAS | Tubeless kit (liquid, valves, levers, manual, tool) |

Suggested Retail Price (CDN): \$4,899.00

FRAME GEOMETRY

| FRAME | XS | S | M | ML |
|--------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 420 | 450 | 475 | 500 |
| Seat Tube Angle | 75.0° | 75.0° | 74.0° | 74.0° |
| Top Tube Length (mm) | 550 | 560 | 570 | 580 |
| Head Tube Length (mm) | 135 | 135 | 150 | 165 |
| Head Tube Angle | 71.0° | 71.0° | 71.0° | 71.0° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 |
| Trail (mm) | 66 | 66 | 66 | 66 |
| Wheelbase (mm) | 1069 | 1078 | 1079 | 1090 |
| Chain Stay Length (mm) | 455 | 455 | 455 | 455 |
| Bottom Bracket Drop (mm) | 75 | 75 | 75 | 75 |
| Stack (mm) | 563 | 563 | 577 | 592 |
| Reach (mm) | 399 | 408 | 404 | 410 |
| Stand Over Height (mm) | 702 | 717 | 734 | 753 |
| Handlebar Width (mm) | 400 | 400 | 420 | 420 |
| Stem Length (mm) | 60 | 60 | 60 | 60 |
| Crank Length (mm) | 170 | 170 | 170 | 170 |
| Wheel Size | 700C | 700C | 700C | 700C |

All prices and specifications are subject to change without notice.