



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Cold Night/Aged Denim
RAHMEN	ALUXX-Grade Aluminum, 12x142mm thru-axle, disc, flip chip dropout
GABEL	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIFFE	cork tape with gel
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
SATTELSTÜTZE	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SATTEL	Giant Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM Rival 1, 1x11
UMWERFER	N/A
SCHALTWERK	SRAM Rival 1
BREMSSEN	SRAM Rival 1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BREMSHEBEL	SRAM Rival 1, left lever dropper switch
KASSETTE	SRAM Rival, 11-speed, 11x42
KETTE	SRAM PC-1130
KURBEL	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175m
TRETLAGER	SRAM DUB, threaded

LAUFRÄDER	
FELGEN	Giant XCT-1 Disc WheelSystem
NABE	Shimano cup and cone
SPEICHEN	stainless
REIFEN	Giant CrossCut Grip 1, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sitzrohrlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	74.0° 73.9°	73.5° 73.4°	73.5° 73.4°	73.0° 72.9°	73.0° 72.9°	73.0° 72.9°
Oberrohrlänge (mm)	543	553	560	575	585	600
Steuerrohr-Länge (mm)	90	100	115	130	145	160
Steuerrohr-Winkel	70.5° 70.4°	71.0° 70.9°	71.5° 71.4°	72.0° 71.9°	72.0° 71.9°	72.0° 71.9°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	80.3 83.7	76.9 80.3	73.5 76.8	70.1 73.4	70.1 73.4	70.1 73.4
Radstand (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041 1051	1051 1061
Kettenstreben-Länge (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Tretlager-Höhe (mm)	68 69	68 69	68 69	68 69	68 69	68 69
Stack (mm)	549	560	576	592	607	621
Reach (mm)	386	387	389	393	399	410
Überstandshöhe (mm)	714 720	734 737	750 756	767 773	785 792	803 809
Lenkerbreite (mm)	440	440	460	460	480	480
Vorbaulänge (mm)	50	60	70	80	80	80
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700c	700c	700c	700c	700c

Spezifikations-, Preis- und Farbänderungen vorbehalten.