REVOLT X 1



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Cold Night/Aged Denim
CUADRO	ALUXX-Grade Aluminum, 12x142mm thru-axle, disc, flip chip dropout
TIJERA	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	cork tape with gel
POTENCIA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
POSTE DE ASIENTO	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
ASIENTO	Giant Approach
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Rival 1, 1x11
DESVIADOR	N/A
CAMBIO TRASERO	SRAM Rival 1
FRENOS	SRAM Rival 1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	SRAM Rival 1, left lever dropper switch
CASSETTE	SRAM Rival, 11-speed, 11x42
CADENA	SRAM PC-1130
MULTIPLICACIÓN	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175m
EJE DE CENTRO	SRAM DUB, threaded

RUEDAS	
RUEDAS	Giant XCT-1 Disc WheelSystem
MAZAS	Shimano cup and cone
RAYOS	stainless
NEUMÁTICOS	Giant CrossCut Grip 1, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Precio: $75,900.00

GEOMETRÍA

CUADRO	XS	S	M	ML
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Longitud de la Base del Poste de Asiento (mm)	430	450	470	490
Ángulo de la Base del Poste de Asiento	74.0° | 73.9°	73.5° | 73.4°	73.5° | 73.4°	73.0° | 72.9°
Longitud del Tubo Superior (mm)	543	553	560	575
Longitud del Telescopio (mm)	90	100	115	130
Ángulo del Telescopio	70.5° | 70.4°	71.0° | 70.9°	71.5° | 71.4°	72.0° | 71.9°
Rake (mm)	50	50	50	50
Trail (mm)	80.3 | 83.7	76.9 | 80.3	73.5 | 76.8	70.1 | 73.4
Distancia entre Ejes (mm)	1023 | 1033	1024 | 1034	1026 | 1036	1031 | 1041
Longitud de Vaina Inferior (mm)	425 | 435	425 | 435	425 | 435	425 | 435
Caída del Eje de Centro (mm)	68 | 69	68 | 69	68 | 69	68 | 69
Stack (mm)	549	560	576	592
Reach (mm)	386	387	389	393
Altura del Tubo Superior al Suelo (mm)	714 | 720	734 | 737	750 | 756	767 | 773
Ancho del Manubrio (mm)	440	440	460	460
Longitud de la Potencia (mm)	50	60	70	80
Longitud de la Biela (mm)	170	170	172.5	172.5
Tamaño de las Ruedas	700C	700c	700c	700c

Todas las especificaciones están sujetas a cambios sin previo aviso.