



## SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Cold Night/Aged Denim
RAMME	ALUXX-Grade Aluminum, 12x142mm thru-axle, disc, flip chip dropout
GAFFEL	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	cork tape with gel
STYRSTEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
SETEPINNE	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SADEL	Giant Approach
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM Rival 1, 1x11
FRONTGIR	N/A
BAKGIR	SRAM Rival 1
BREMSE	SRAM Rival 1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BREMSEHENDLER	SRAM Rival 1, left lever dropper switch
KASSETT	SRAM Rival, 11-speed, 11x42
KJEDE	SRAM PC-1130
KRANK	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175m
BOTTOM BRACKET	SRAM DUB, threaded

HJUL	
FELG	Giant XCT-1 Disc WheelSystem
NAV	Shimano cup and cone
EIKE	stainless
DEKK	Giant CrossCut Grip 1, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

## GEOMETRI

RAMME	XS	S	M	ML	L	XL
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0°   73,9°	73,5°   73,4°	73,5°   73,4°	73,0°   72,9°	73,0°   72,9°	73,0°   72,9°
Top Tube Length (mm)	543	553	560	575	585	600
Head Tube Length (mm)	90	100	115	130	145	160
Head Tube Angle	70,5°   70,4°	71,0°   70,9°	71,5°   71,4°	72,0°   71,9°	72,0°   71,9°	72,0°   71,9°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	80,3   83,7	76,9   80,3	73,5   76,8	70,1   73,4	70,1   73,4	70,1   73,4
Wheelbase (mm)	1023   1033	1024   1034	1026   1036	1031   1041	1041   1051	1051   1061
Chain Stay Length (mm)	425   435	425   435	425   435	425   435	425   435	425   435
Bottom Bracket Drop (mm)	68   69	68   69	68   69	68   69	68   69	68   69
Stack (mm)	549	560	576	592	607	622
Reach (mm)	386	387	389	393	399	410
Stand Over Height (mm)	714   720	734   737	750   756	767   773	785   792	803   810
Handlebar Width (mm)	440	440	460	460	480	480
Stem Length (mm)	50	60	70	80	80	80
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700c	700c	700c	700c	700c

Alle spesifikasjonene kan endres uten varsel.