

REVOLT X 1

GIANT



SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L, XL
CORES	Panther/Helios Orange
QUADRO	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
FORQUILHA	RockShox Rudy XPLR, 40mm, cartridge damper12x100mm thru-axle
AMORTECEDORES	N/A
COMPONENTES	
GUIADOR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
PUNHOS	cork tape with gel
AVANÇO	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
ESPIGÃO DE SELIM	Post Moderne suspension dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SELIM	Giant Approach
PEDAIS	N/A
TRANSMISSÃO	
MANETES	SRAM Apex, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	Sram X1 Eagle 1X12
TRAVÕES	SRAM hydraulic, Giant MPH rotors [F]160mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Sram Apex 1X12 HRD (hydraulic road disc), left lever dropper switch
CASSETTE	SRAM PG-1210, 12-speed, 11x50
CORRENTE	SRAM CN-EAGL-NX-A1, 12-speed
CONJUNTO PEDALEIRO	SRAM Apex 1 Wide, DUB 1X 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant P-X2 EVO Disc wheelset
CUBOS	Alloy
RAIOS	Stainless
PNEUS	Crosscut GRIP 700x45c, tubeless prepared
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Preço: 2 649,00 €

GEOMETRIA

QUADRO	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Comprimento do tubo do assento (mm)	430		450		470		490		510		530	
Ângulo do tubo do assento	74,0°	73,9°	73,5°	73,4°	73,5°	73,4°	73,0°	72,9°	73,0°	72,9°	73,0°	73,0°
Comprimento do tubo superior (mm)	543		553		560		575		585		600	
Comprimento do tubo principal (mm)	90		100		115		130		145		160	
Ângulo do tubo principal	70,5°	70,4°	71,0°	70,9°	71,5°	71,4°	72,0°	71,9°	72,0°	71,9°	72,0°	72,0°
Garfo ancinho (mm)	50		50		50		50		50		50	
Trilha (mm)	80,3	83,7	76,9	80,3	73,5	76,8	70,1	73,4	70,1	73,4	70,1	70,1
distância entre eixos (mm)	1023	1033	1024	1034	1026	1036	1031	1041	1041	1051	1051	1051
Comprimento Chain Stay (mm)	425	435	425	435	425	435	425	435	425	435	425	425
Suporte inferior (mm)	68	69	68	69	68	69	68	69	68	69	68	68
Pilha (mm)	549		560		576		592		607		621	
Alcançar (mm)	386		387		389		393		399		410	
Altura do standover (mm)	714	720	734	737	750	756	767	773	785	792	805	805
Largura do guidão (mm)	440		440		460		460		480		480	480
Comprimento da haste (mm)	50		60		70		80		80		90	
Comprimento da Manivela (mm)	170		170		172,5		172,5		175		175	175
Tamanho da roda	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	700x 42C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.