



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Cold Night/Aged Denim
OKVIR	ALUXX-Grade Aluminum, 12x142mm thru-axle, disc, flip chip dropout
VILICE	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	cork tape with gel
OPORA KRMILA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
OPORA SEDEŽA	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SEDEŽ	Giant Approach
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM Rival 1, 1x11
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM Rival 1
ZAVORE	SRAM Rival 1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Rival 1, left lever dropper switch
VERIŽNIK	SRAM Rival, 11-speed, 11x42
VERIGA	SRAM PC-1130
GONILKE Z VERIŽNIKI	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175m
BOTTOM BRACKET	SRAM DUB, threaded

OBROČNIKI	
OBROČI	Giant XCT-1 Disc WheelSystem
PESTA	Shimano cup and cone
NAPERE	stainless
PLAŠČI	Giant CrossCut Grip 1, 700x45c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

## GEOMETRIJA

OKVIR	XS	S	M	ML	L
Dolžina sedežne cevi (mm)	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Kot sedežne cevi	74,0°   73,9°	73,5°   73,4°	73,5°   73,4°	73,0°   72,9°	72,5°   72,4°
Top Tube Length (mm)	543	553	560	575	585
Višina glave okvirja (mm)	90	100	115	130	145
Krmilni kot	70,5°   70,4°	71,0°   70,9°	71,5°   71,4°	72,0°   71,9°	72,5°   72,4°
Zamik vpetja osi (mm)	50	50	50	50	50
Trail (mm)	80,3   83,7	76,9   80,3	73,5   76,8	70,1   73,4	66,7   70,0
Medosna razdalja (mm)	1023   1033	1024   1034	1026   1036	1031   1041	1036   1046
Dolžina cevi ob verigi (mm)	425   435	425   435	425   435	425   435	425   435
Bottom Bracket Drop (mm)	68   69	68   69	68   69	68   69	68   69
Oddaljenost zgornje cevi od gonilne osi (mm)	549	560	576	592	608
Doseg (mm)	386	387	389	393	397
Višina zgornje cevi (mm)	714   720	734   737	750   756	767   773	784   790
Širina krmila (mm)	440	440	460	460	460
Dolžina opore krmila (mm)	50	60	70	80	90
Dolžina gonilke (mm)	170	170	172,5	172,5	175
Velikost obročnikov	700C	700c	700c	700c	700c

Vse navedene specifikacije se lahko spremenijo brez obvestila.