

REVOLT X ADVANCED PRO 0



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, M/L, L, XL
FARVER	Kelp Forest/Charcoal/Chrome
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORGAFFEL	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper12x100mm thru-axle
BAGDÆMPER	N/A
KOMPONENTER	
STYR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SADELPIND	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SADEL	Giant Approach SL
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	SRAM Force eTap AXS, 1x12
FORSKIFTER	N/A
BAGSKIFTER	SRAM X01 Eagle AXS
BREMSE	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BREMSEGREB	SRAM Force eTap AXS hydraulic
KASSETTE	SRAM XG-1295, 12-speed, 10x52
KÆDE	SRAM X01 Eagle
KRANKSÆT	SRAM FORCE 1 Wide, DUB 1x 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAV	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
EGER	Sapim Laser
DÆK	Maxxis Rambler, 700x50c, tubeless prepared
EKSTRA	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Pris: 58.499,00 kr.

GEOMETRI

RAMME	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sadelrørslængde (mm)	430		450		470		490		510		530	
Sadelrørsvinkel	74,0°	73,9°	73,5°	73,4°	73,5°	73,4°	73,0°	72,9°	73,0°	72,9°	73,0°	72,9°
Overrørslængde (mm)	543		553		560		575		585		600	
Kronrørslængde (mm)	90		100		115		130		145		160	
Kronrørsvinkel	70,5°	70,4°	71,0°	70,9°	71,5°	71,4°	72,0°	71,9°	72,0°	71,9°	72,0°	71,9°
Forgaffel fremspring (rake) (mm)	50		50		50		50		50		50	
Sti (mm)	80,3	83,7	76,9	80,3	73,5	76,8	70,1	73,4	70,1	73,4	70,1	73,4
Akselafstand (mm)	1023	1033	1024	1034	1026	1036	1031	1041	1041	1051	1057	1067
Kædestagslængde (mm)	425	435	425	435	425	435	425	435	425	435	425	435
Krankboks drop (mm)	68	69	68	69	68	69	68	69	68	69	68	69
Stack (mm)	549		560		576		592		607		621	
Reach (mm)	386		387		389		393		399		410	
Skridthøjde (mm)	720	726	736	743	755	761	772	778	790	796	808	814
Styrbredde (mm)	440		440		460		460		480		480	
Frempindslængde (mm)	50		60		70		80		80		90	
Pedalarmslængde (mm)	170		170		172,5		172,5		175		175	
Hjulstørrelse	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

Alle de anførte specifikationer kan ændres uden varsel.