

REVOLT X ADVANCED PRO 0

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, M/L, L, XL
FARVER	Interstellar/Carbon
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORGAFFEL	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper 12x100mm thru-axle
KOMPONENTER	
SADELPIND	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SADEL	Giant Approach SL
GEARGRUPPE	
SKIFTEGREB	SRAM Force eTap AXS, 1x12
BAGSKIFTER	SRAM X01 Eagle AXS
BREMSE	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BREMSEGREB	SRAM Force eTap AXS hydraulic
KASSETTE	SRAM XG-1295, 12-speed, 10x52
KÆDE	SRAM X01 Eagle
KRANKSÆT	SRAM FORCE 1 Wide, DUB 1X 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAV	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
EGER	Sapim Laser
DÆK	Maxxis Rambler, 700x50c, tubeless prepared
EKSTRA	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
GRÆNSER	
MAX DÆKSTØRRELSE	53mm

Pris: 58.499,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Sadelrørslængde (mm)	450	470	490	510	530
Sadelrørvinkel	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°
Overrørslængde (mm)	553	560	575	585	600
Kronrørslængde (mm)	100	115	130	145	160
Kronrørvinkel	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	76,9 80,3	73,5 76,8	70,1 73,4	70,1 73,4	70,1 73,4
Akselafstand (mm)	1024 1034	1026 1036	1031 1041	1041 1051	1057 1067
Kædestagslængde (mm)	425 435	425 435	425 435	425 435	425 435
Krankboks drop (mm)	68 69	68 69	68 69	68 69	68 69
Stack (mm)	560	576	592	607	621
Reach (mm)	387	389	393	399	410
Skridthøjde (mm)	736 743	755 761	772 778	790 796	808 814
Styrbredde (mm)	440	460	460	480	480
Frempindslængde (mm)	60	70	80	80	90
Pedalarmslængde (mm)	170	172,5	172,5	175	175
Hjulstørrelse	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Alle de anførte specifikationer kan ændres uden varsel.