

REVOLT X ADVANCED PRO 0

GIANT



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLOURS	Gloss Kelp Forest/Charcoal/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper12x100mm thru-axle
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 31.8mm S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SEATPOST	Post Moderne, dropper, 30.9mm with 30mm of suspension S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SADDLE	Giant Approach SL
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM X01 Eagle AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM XG-1295, 12-speed, 10x52
CHAIN	SRAM X01 Eagle
CRANKSET	SRAM Force D1 DUB, 40t S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
HUBS	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Laser
TYRES	Maxxis Rambler, 700x50c, tubeless prepared
EXTRAS	Factory tubeless set up, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position
LIMITS	
MAX CHAINRING SIZE	SRAM Wide 1x 44T. Shimano GRX 1x 42T

Price: €7,449.00

GEOMETRY

FRAME	S	M	ML	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	450	470	490	530
Seat Tube Angle	73.5° 73.4°	73.5° 73.4°	73.0° 72.9°	73.0° 72.9°
Top Tube Length (mm)	553	560	575	600
Head Tube Length (mm)	100	115	130	160
Head Tube Angle	71.0° 70.9°	71.5° 71.4°	72.0° 71.9°	72.0° 71.9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	76.9 80.3	73.5 76.8	70.1 73.4	70.1 73.4
Wheelbase (mm)	1024 1034	1026 1036	1031 1041	1057 1067
Chain Stay Length (mm)	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69
Stack (mm)	560	576	592	621
Reach (mm)	387	389	393	410
Stand Over Height (mm)	736 743	755 761	772 778	808 814
Handlebar Width (mm)	440	460	460	480
Stem Length (mm)	60	70	80	90
Crank Length (mm)	170	172.5	172.5	175
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C

All specifications listed are subject to change without notice.