

REVOLT X ADVANCED PRO 0

GIANT



TEKNISET TIEDOT

| RUNKO          |                                                                                                 |
|----------------|-------------------------------------------------------------------------------------------------|
| KOOT           | XS, S, M, M/L, L, XL                                                                            |
| VÄRIT          | Kelp Forest/Charcoal/Chrome                                                                     |
| RUNKO          | Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout                           |
| HAARUKKA       | Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper12x100mm thru-axle                         |
| ISKUNVAIMENNIN | N/A                                                                                             |
| KOMONENTIT     |                                                                                                 |
| OHJAUSTANKO    | Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm           |
| GRIPIT         | Stratus Lite 3.0                                                                                |
| OHJAINKANNATIN | Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm                      |
| SATULATOLPPA   | Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop |
| SATULA         | Giant Approach SL                                                                               |
| POLKIMET       | N/A                                                                                             |
| VOIMANSIIRTO   |                                                                                                 |
| VAIHDEVIPU     | SRAM Force eTap AXS, 1x12                                                                       |
| ETUVAIHTAJA    | N/A                                                                                             |
| TAKAVAIHTAJA   | SRAM X01 Eagle AXS                                                                              |
| JARRUT         | SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm                        |
| JARRUKAHVAT    | SRAM Force eTap AXS hydraulic                                                                   |
| RATASPAKKA     | SRAM XG-1295, 12-speed, 10x52                                                                   |
| KETJUT         | SRAM X01 Eagle                                                                                  |
| KAMPISARJA     | SRAM FORCE 1 Wide, DUB 1X 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm      |
| KESKIÖ         | SRAM DUB, press fit                                                                             |

| RENKAAT    |                                                                                                                          |
|------------|--------------------------------------------------------------------------------------------------------------------------|
| VANTEET    | Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm                                                                         |
| NAVAT      | [F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle |
| PINNAT     | Sapim Laser                                                                                                              |
| RENKAAT    | Maxxis Rambler, 700x50c, tubeless prepared                                                                               |
| LISÄTIEDOT | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position     |

Suositusinta: 7 879,00 €

GEOMETRIA

| RUNKO                              | S        |          | M        |          | ML       |          | L        |          | XL    |       |
|------------------------------------|----------|----------|----------|----------|----------|----------|----------|----------|-------|-------|
|                                    | LOW      | HIGH     | LOW      | HIGH     | LOW      | HIGH     | LOW      | HIGH     | LOW   | HIGH  |
| Satulaputken pituus (mm)           | 450      | 470      | 470      | 490      | 490      | 510      | 510      | 530      |       |       |
| Satulaputken kulma                 | 73,5°    | 73,4°    | 73,5°    | 73,4°    | 73,0°    | 72,9°    | 73,0°    | 72,9°    | 73,0° | 72,9° |
| Vaakaputken pituus (mm)            | 553      | 560      | 560      | 575      | 575      | 585      | 585      | 600      |       |       |
| Emäputken pituus (mm)              | 100      | 115      | 115      | 130      | 130      | 145      | 145      | 160      |       |       |
| Emäputken kulma                    | 71,0°    | 70,9°    | 71,5°    | 71,4°    | 72,0°    | 71,9°    | 72,0°    | 71,9°    | 72,0° | 71,9° |
| Haarukan offset (mm)               | 50       | 50       | 50       | 50       | 50       | 50       | 50       | 50       |       |       |
| Trail-mitta (mm)                   | 76,9     | 80,3     | 73,5     | 76,8     | 70,1     | 73,4     | 70,1     | 73,4     | 70,1  | 73,4  |
| Akseliväli (mm)                    | 1024     | 1034     | 1026     | 1036     | 1031     | 1041     | 1041     | 1051     | 1057  | 1067  |
| Takahaarukan alaputken pituus (mm) | 425      | 435      | 425      | 435      | 425      | 435      | 425      | 435      | 425   | 435   |
| Keskiön pudotus (mm)               | 68       | 69       | 68       | 69       | 68       | 69       | 68       | 69       | 68    | 69    |
| Stack-mitta (mm)                   | 560      | 576      | 576      | 592      | 592      | 607      | 607      | 621      |       |       |
| Reach-mitta (mm)                   | 387      | 389      | 389      | 393      | 393      | 399      | 399      | 410      |       |       |
| Standover-mitta (mm)               | 736      | 743      | 755      | 761      | 772      | 778      | 790      | 796      | 808   | 814   |
| Ohjaustangon leveys (mm)           | 440      | 460      | 460      | 460      | 460      | 480      | 480      | 480      |       |       |
| Ohjainkannattimen pituus (mm)      | 60       | 70       | 70       | 80       | 80       | 80       | 80       | 90       |       |       |
| Kammen pituus (mm)                 | 170      | 172,5    | 172,5    | 172,5    | 172,5    | 175      | 175      | 175      |       |       |
| Rengaskoko                         | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C |       |       |

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.