

# REVOLT X ADVANCED PRO 0

GIANT



## TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, M/L, L, XL
VÄRIT	Interstellar/Carbon
RUNKO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
HAARUKKA	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper/12x100mm thru-axle
KOMONENTIT	
SATULATOLPPA	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SATULA	Giant Approach SL
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Force eTap AXS, 1x12
TAKAVAIHTAJA	SRAM X01 Eagle AXS
JARRUT	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
JARRUKAHVAT	SRAM Force eTap AXS hydraulic
RATASPAKKA	SRAM XG-1295, 12-speed, 10x52
KETJUT	SRAM X01 Eagle
KAMPISARJA	SRAM FORCE 1 Wide, DUB 1X 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAVAT	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
PINNAT	Sapim Laser
RENKAAT	Maxxis Rambler, 700x50c, tubeless prepared
LISÄTIEDOT	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
RAJOITTEET	
MAX RENGASVARA	53mm

Suositusuhinta: 7 879,00 €

## GEOMETRIA

RUNKO	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Satulaputken pituus (mm)	450	470	490	510	530
Satulaputken kulma	73,5°   73,4°	73,5°   73,4°	73,0°   72,9°	73,0°   72,9°	73,0°   7
Vaakaputken pituus (mm)	553	560	575	585	600
Emäputken pituus (mm)	100	115	130	145	160
Emäputken kulma	71,0°   70,9°	71,5°   71,4°	72,0°   71,9°	72,0°   71,9°	72,0°   7
Haarukan offset (mm)	50	50	50	50	50
Trail-mitta (mm)	76,9   80,3	73,5   76,8	70,1   73,4	70,1   73,4	70,1   73
Akseliväli (mm)	1024   1034	1026   1036	1031   1041	1041   1051	1057   1
Takahaarukan alaputken pituus (mm)	425   435	425   435	425   435	425   435	425   43
Keskiön pudotus (mm)	68   69	68   69	68   69	68   69	68   69
Stack-mitta (mm)	560	576	592	607	621
Reach-mitta (mm)	387	389	393	399	410
Standover-mitta (mm)	736   743	755   761	772   778	790   796	808   81
Ohjaustangon leveys (mm)	440	460	460	480	480
Ohjainkannattimen pituus (mm)	60	70	80	80	90
Kammen pituus (mm)	170	172,5	172,5	175	175
Rengaskoko	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.