



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Interstellar/Carbon
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper12x100mm thru-axle
ONDERDELEN	
ZADELPEEN	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
ZADEL	Giant Approach SL
AFMONTAGE	
SHIFTERS	SRAM Force eTap AXS, 1x12
ACHTERDERAILLEUR	SRAM X01 Eagle AXS
REMMEN	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM XG-1295, 12-speed, 10x52
AANDRIJVING	SRAM X01 Eagle
CRANKSET	SRAM FORCE 1 Wide, DUB 1X 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAVEN	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim Laser
BANDEN	Maxxis Rambler, 700x50c, tubeless prepared
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAXIMALE BANDENVRIJHEID	53mm

Adviesprijs: € 7.599,00

GEOMETRIE

FRAME	S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	450		470		490		510		530	
Zitbuis Hoek	73,5° 73,4°		73,5° 73,4°		73,0° 72,9°		73,0° 72,9°		73,0° 72,9°	
Frame Lengte (horizontaal) (mm)	553		560		575		585		600	
Balhoofdbuis Lengte (mm)	100		115		130		145		160	
Balhoofdbuis Hoek	71,0° 70,9°		71,5° 71,4°		72,0° 71,9°		72,0° 71,9°		72,0° 71,9°	
Vork Sprong (mm)	50		50		50		50		50	
Naloop (mm)	76,9 80,3		73,5 76,8		70,1 73,4		70,1 73,4		70,1 73,4	
Wielbasis (mm)	1024 1034		1026 1036		1031 1041		1041 1051		1057 1067	
Liggende achtersvork lengte (mm)	425 435		425 435		425 435		425 435		425 435	
Bottom Bracket Drop (mm)	68 69		68 69		68 69		68 69		68 69	
Stack (mm)	560		576		592		607		621	
Reach (mm)	387		389		393		399		410	
Stand Over Height (mm)	736 743		755 761		772 778		790 796		808 814	
Stuur breedte (mm)	440		460		460		480		480	
Stuurpen Lengte (mm)	60		70		80		80		90	
Cranklengte (mm)	170		172,5		172,5		175		175	
Wielmaat	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.