

REVOLT X ADVANCED PRO 0



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Airglow/Black Curreant
CADRE	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FOURCHE	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper 12x100mm thru-axle
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
TIGE DE SELLE	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SELLE	Giant Approach SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	SRAM Force eTap AXS, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM X01 Eagle AXS
FREINS	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors[F]160mm, [R]160mm
LEVIERS DE FREIN	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM XG-1295, 12-speed, 10x52
CHAÎNE	SRAM X01 Eagle
PÉDALIER	SRAM Force D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
MOYEUX	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Sapim Laser
PNEUS	Maxxis Rambler, 700x50c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 7 800,00 €

GÉOMÉTRIE

CADRE	S		M		ML		L		XL	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Longueur de tube de selle (mm)	450	470	490	510	530					
Angle de tube de selle	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°
Longueur du tube supérieur (mm)	553	560	575	585	600					
Longueur du tube de direction (mm)	100	115	130	145	160					
Angle du tube de direction	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°
Déport de fourche (mm)	50	50	50	50	50					
Trail (mm)	76,9 80,3	73,5 76,8	70,1 73,4	70,1 73,4	70,1 73,4	70,1 73,4	70,1 73,4	70,1 73,4	70,1 73,4	70,1 73,4
Empattement (mm)	1024 1034	1026 1036	1031 1041	1041 1051	1057 1107					
Longueur des bases (mm)	425 435	425 435	425 435	425 435	425 435					
Drop du boîtier de pédalier (mm)	68 69	68 69	68 69	68 69	68 69					
Stack (mm)	560	576	592	607	621					
Reach (mm)	387	389	393	399	410					
Hauteur en statique (mm)	734 737	750 756	767 773	785 792	803 810					
Largeur de cintre (mm)	440	460	460	480	480					
Longueur de potence (mm)	60	70	80	80	80					
Longueur des manivelles (mm)	170	172,5	172,5	175	175					
Diamètre des roues	700c	700c	700c	700c	700c					

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.