

REVOLT X ADVANCED PRO 0



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Airglow/Black Currant
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper 12x100mm thru-axle
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
SEATPOST	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SADDLE	Giant Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM X01 Eagle AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors[F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM XG-1295, 12-speed, 10x52
CHAIN	SRAM X01 Eagle
CRANKSET	SRAM Force D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
HUBS	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Laser
TIRES	Maxxis Rambler, 700x50c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0° 73,9°	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°
Top Tube Length (mm)	543	553	560	575	585	600
Head Tube Length (mm)	90	100	115	130	145	160
Head Tube Angle	70,5° 70,4°	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	80,3 83,7	76,9 80,3	73,5 76,8	70,1 73,4	70,1 73,4	70,1 73,4
Wheelbase (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041 1051	1051 1061
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69	68 69
Stack (mm)	549	560	576	592	607	622
Reach (mm)	386	387	389	393	399	410
Stand Over Height (mm)	714 720	734 737	750 756	767 773	785 792	803 810
Handlebar Width (mm)	440	440	460	460	480	480
Stem Length (mm)	50	60	70	80	80	80
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700c	700c	700c	700c	700c

All specifications listed are subject to change without notice.