

REVOLT X ADVANCED PRO 0

GIANT



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Kelp Forest/Charcoal/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper 12x100mm thru-axle
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
ZADELPEN	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
ZADEL	Giant Approach SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM Force eTap AXS, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM X01 Eagle AXS
REMMEN	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM XG-1295, 12-speed, 10x52
AANDRIJVING	SRAM X01 Eagle
CRANKSET	SRAM FORCE 1 Wide, DUB 1x 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAVEN	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim Laser
BANDEN	Maxxis Rambler, 700x50c, tubeless prepared
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Adviesprijs: € 7.599,00

GEOMETRIE

FRAME	XS	S	M	ML	L	
Zitbuis Lengte (mm)	SHORT LONG SHORT	430	450	470	490	510
Zitbuis Hoek	74,0° 73,9°	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°	
Frame Lengte (horizontaal) (mm)	543	553	560	575	585	
Balhoofdbuis Lengte (mm)	90	100	115	130	145	
Balhoofdbuis Hoek	70,5° 70,4°	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°	
Vork Sprong (mm)	50	50	50	50	50	
Naloop (mm)	80,3 83,7	76,9 80,3	73,5 76,8	70,1 73,4	70,1 73,4	
Wielbasis (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041 1051	
Liggende achtervork lengte (mm)	425 435	425 435	425 435	425 435	425 435	
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69	
Stack (mm)	549	560	576	592	607	
Reach (mm)	386	387	389	393	399	
Stand Over Height (mm)	720 726	736 743	755 761	772 778	790 796	
Stuur breedte (mm)	440	440	460	460	480	
Stuurpen Lengte (mm)	50	60	70	80	80	
Cranklengte (mm)	170	170	172,5	172,5	175	
Wielmaat	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.