

REVOLT X ADVANCED PRO 0

GIANT



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Airglow/Black Currant
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper 12x100mm thru-axle
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
ZADELPEN	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
ZADEL	Giant Approach SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM Force eTap AXS, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM X01 Eagle AXS
REMMEN	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors[F]160mm, [R]160mm
REMHENDELS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM XG-1295, 12-speed, 10x52
AANDRIJVING	SRAM X01 Eagle
CRANKSET	SRAM Force D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
NAVEN	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim Laser
BANDEN	Maxxis Rambler, 700x50c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Adviesprijs: € 7.499,00

GEOMETRIE

FRAME	XS	S	M	ML	L
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Zitbuis lengte (mm)	430	450	470	490	510
Zitbuis hoek	74,0° 73,9°	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°
Frame Lengte (horizontaal) (mm)	543	553	560	575	585
Balhoofdbuis Lengte (mm)	90	100	115	130	145
Balhoofdbuis Hoek	70,5° 70,4°	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	80,3 83,7	76,9 80,3	73,5 76,8	70,1 73,4	70,1 73,4
Wielbasis (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041 1051
Liggende achtervork lengte (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69
Stack (mm)	549	560	576	592	607
Reach (mm)	386	387	389	393	399
Stand Over Height (mm)	714 720	734 737	750 756	767 773	785 792
Stuur breedte (mm)	440	440	460	460	480
Stuurpen Lengte (mm)	50	60	70	80	80
Cranklengte (mm)	170	170	172,5	172,5	175
Wielmaat	700C	700c	700c	700c	700c

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.