

REVOLT X ADVANCED PRO 0

GIANT



SPECIFICATIES

| FRAME | |
|------------------|---|
| MATEN | XS, S, M, M/L, L, XL |
| KLEUREN | Kelp Forest/Charcoal/Chrome |
| FRAME | Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout |
| VOORVORK | Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper 12x100mm thru-axle |
| DEMPER | N/A |
| ONDERDELEN | |
| STUUR | Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm |
| HANDVATTEN | Stratus Lite 3.0 |
| STUURPEN | Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm |
| ZADELPEN | Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop |
| ZADEL | Giant Approach SL |
| PEDALEN | N/A |
| AFMONTAGE | |
| SHIFTERS | SRAM Force eTap AXS, 1x12 |
| VOORDERAILLEUR | N/A |
| ACHTERDERAILLEUR | SRAM X01 Eagle AXS |
| REMMEN | SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm |
| REMHENDELS | SRAM Force eTap AXS hydraulic |
| CASSETTE | SRAM XG-1295, 12-speed, 10x52 |
| AANDRIJVING | SRAM X01 Eagle |
| CRANKSET | SRAM FORCE 1 Wide, DUB 1x 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | SRAM DUB, press fit |

| WIELSET | |
|---------|--|
| VELGEN | Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm |
| NAVEN | [F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle |
| SPAKEN | Sapim Laser |
| BANDEN | Maxxis Rambler, 700x50c, tubeless prepared |
| EXTRA'S | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position |

Adviesprijs: € 7.599,00

GEOMETRIE

| FRAME | XS | S | M | ML | L |
|---------------------------------|--------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Zitbuis lengte (mm) | SHORT LONG SHORT | LONG SHORT LONG SHORT | LONG SHORT LONG SHORT | LONG SHORT LONG SHORT | LONG SHORT LONG SHORT |
| Zitbuis hoek | 74,0° 73,9° | 73,5° 73,4° | 73,5° 73,4° | 73,0° 72,9° | 73,0° 72,9° |
| Frame Lengte (horizontaal) (mm) | 543 | 553 | 560 | 575 | 585 |
| Balhoofdbuis Lengte (mm) | 90 | 100 | 115 | 130 | 145 |
| Balhoofdbuis Hoek | 70,5° 70,4° | 71,0° 70,9° | 71,5° 71,4° | 72,0° 71,9° | 72,0° 71,9° |
| Vork Sprong (mm) | 50 | 50 | 50 | 50 | 50 |
| Naloop (mm) | 80,3 83,7 | 76,9 80,3 | 73,5 76,8 | 70,1 73,4 | 70,1 73,4 |
| Wielbasis (mm) | 1023 1033 | 1024 1034 | 1026 1036 | 1031 1041 | 1041 1051 |
| Liggende achtervork lengte (mm) | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 |
| Bottom Bracket Drop (mm) | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 |
| Stack (mm) | 549 | 560 | 576 | 592 | 607 |
| Reach (mm) | 386 | 387 | 389 | 393 | 399 |
| Stand Over Height (mm) | 720 726 | 736 743 | 755 761 | 772 778 | 790 796 |
| Stuur breedte (mm) | 440 | 440 | 460 | 460 | 480 |
| Stuurpen Lengte (mm) | 50 | 60 | 70 | 80 | 80 |
| Cranklengte (mm) | 170 | 170 | 172,5 | 172,5 | 175 |
| Wielmaat | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.