

REVOLT X ADVANCED PRO 0



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Interstellar/Carbon
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper 12x100mm thru-axle
ONDERDELEN	
ZADELPEN	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
ZADEL	Giant Approach SL
AFMONTAGE	
SHIFTERS	SRAM Force eTap AXS, 1x12
ACHTERDERAILLEUR	SRAM X01 Eagle AXS
REMMEN	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM XG-1295, 12-speed, 10x52
AANDRIJVING	SRAM X01 Eagle
CRANKSET	SRAM FORCE 1 Wide, DUB 1X 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAVEN	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim Laser
BANDEN	Maxxis Rambler, 700x50c, tubeless prepared
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

Adviesprijs: € 7.599,00

GEOMETRIE

FRAME	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG
Zitbuis lengte (mm)	450	470	490	510	530
Zitbuis hoek	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°
Frame Lengte (horizontaal) (mm)	553	560	575	585	600
Balhoofdbuis Lengte (mm)	100	115	130	145	160
Balhoofdbuis Hoek	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	76,9 80,3	73,5 76,8	70,1 73,4	70,1 73,4	70,1 73,4
Wielbasis (mm)	1024 1034	1026 1036	1031 1041	1041 1051	1057 1067
Liggende achtervork lengte (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69
Stack (mm)	560	576	592	607	621
Reach (mm)	387	389	393	399	410
Stand Over Height (mm)	736 743	755 761	772 778	790 796	808 814
Stuur breedte (mm)	440	460	460	480	480
Stuurpen Lengte (mm)	60	70	80	80	90
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.