REVOLT X ADVANCED PRO 0



SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	Airglow/Black Currant
CADRU	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FURCA	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper 12x100mm thru-axle
SOC	N/A
COMPONENTE	
GHIDON	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
PIPA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
TIJA SA	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SA	Giant Approach SL
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Force eTap AXS, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	SRAM X01 Eagle AXS
FRANE	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors[F]160mm, [R]160mm
MANETE FRANA	SRAM Force eTap AXS hydraulic
PINIOANE	SRAM XG-1295, 12-speed, 10x52
LANT	SRAM X01 Eagle
ANGRENAJ	SRAM Force D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
BUTUCI	F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPITE	Sapim Laser
ANVELOPE	Maxxis Rambler, 700x50c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

GEOMETRIE

CADRU	XS	S	M	ML	L	XL
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG	SH
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0° | 73,9°	73,5° | 73,4°	73,5° | 73,4°	73,0° | 72,9°	73,0° | 72,9°	73,
Top Tube Length (mm)	543	553	560	575	585	600
Head Tube Length (mm)	90	100	115	130	145	160
Head Tube Angle	70,5° | 70,4°	71,0° | 70,9°	71,5° | 71,4°	72,0° | 71,9°	72,0° | 71,9°	72,
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	80,3 | 83,7	76,9 | 80,3	73,5 | 76,8	70,1 | 73,4	70,1 | 73,4	70,
Wheelbase (mm)	1023 | 1033	1024 | 1034	1026 | 1036	1031 | 1041	1041 | 1051	105
Chain Stay Length (mm)	425 | 435	425 | 435	425 | 435	425 | 435	425 | 435	425
Bottom Bracket Drop (mm)	68 | 69	68 | 69	68 | 69	68 | 69	68 | 69	68
Stack (mm)	549	560	576	592	607	621
Reach (mm)	386	387	389	393	399	410
Stand Over Height (mm)	714 | 720	734 | 737	750 | 756	767 | 773	785 | 792	803
Handlebar Width (mm)	440	440	460	460	480	480
Stem Length (mm)	50	60	70	80	80	80
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700c	700c	700c	700c	700

Toate specificatiile enumerate se pot schimba fara notificare prealabila.