

# REVOLT X ADVANCED PRO 0

GIANT



## SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Kelp Forest/Charcoal/Chrome
RAM	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
GAFFEL	Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper12x100mm thru-axle
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:46cm, M:L:46cm, L:48cm, XL:48cm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SADELSTOLPE	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SADEL	Giant Approach SL
PEDALER	N/A
DRIVLINA	
VÄXLAR	SRAM Force eTap AXS, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM X01 Eagle AXS
BROMSAR	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BROMSSPAKAR	SRAM Force eTap AXS hydraulic
KASSETT	SRAM XG-1295, 12-speed, 10x52
KEDJA	SRAM X01 Eagle
VEVPARTI	SRAM FORCE 1 Wide, DUB 1X 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAV	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Sapim Laser
DÄCK	Maxxis Rambler, 700x50c, tubeless prepared
EXTRAFUNKTIONER	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Price: 89 490,00 kr

## GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Vinkel sadelrör	73,5°   73,4°	73,5°   73,4°	73,0°   72,9°	73,0°   72,9°	73,0°   72,9°
Topprörets längd (mm)	553	560	575	585	600
Styrhuvud Längd (mm)	100	115	130	145	160
Vinkel styrhuvud	71,0°   70,9°	71,5°   71,4°	72,0°   71,9°	72,0°   71,9°	72,0°   71,9°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	76,9   80,3	73,5   76,8	70,1   73,4	70,1   73,4	70,1   73,4
Hjulbas (mm)	1024   1034	1026   1036	1031   1041	1041   1051	1057   1067
Kedjestagslängd (mm)	425   435	425   435	425   435	425   435	425   435
Nedre fäste Drop (mm)	68   69	68   69	68   69	68   69	68   69
Stack (mm)	560	576	592	607	621
Reach (mm)	387	389	393	399	410
Stå över höjden (mm)	736   743	755   761	772   778	790   796	808   814
Styrets bredd (mm)	440	460	460	480	480
Stamlängd (mm)	60	70	80	80	90
Vevlängd (mm)	170	172,5	172,5	175	175
Hjulstorlek	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

All specifications listed are subject to change without notice.