

REVOLT X ADVANCED PRO 1

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Pale Olive/Shale Green
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	Fox 32 Float TC, Performance Elite, 40mm, FIT 4 damper, 12x100mm Kabolt thru-axle
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SEATPOST	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SADDLE	Giant Grit SL
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS E1, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle AXS
BRAKES	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival AXS E1 hydraulic
CASSETTE	SRAM XG-1275, 12-speed, 10x52
CHAIN	SRAM GX Eagle
CRANKSET	SRAM Rival XPLR E1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
HUBS	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Laser
TYRES	Giant CrossCut Grip, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

Price: €5,999.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0° 73.9°	73.5° 73.4°	73.5° 73.4°	73.0° 72.9°	73.0° 72.9°	73.0° 72.9°
Top Tube Length (mm)	543	553	560	575	585	600
Head Tube Length (mm)	90	100	115	130	145	160
Head Tube Angle	70.5° 70.4°	71.0° 70.9°	71.5° 71.4°	72.0° 71.9°	72.0° 71.9°	72.0° 71.9°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	80.3 83.7	76.9 80.3	73.5 76.8	70.1 73.4	70.1 73.4	70.1 73.4
Wheelbase (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041 1051	1057 1067
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69	68 69
Stack (mm)	549	560	576	592	607	621
Reach (mm)	386	387	389	393	399	410
Stand Over Height (mm)	720 726	736 743	755 761	772 778	790 796	808 814
Handlebar Width (mm)	440	440	460	460	480	480
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

All specifications listed are subject to change without notice.