

REVOLT X ADVANCED PRO 1



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLORS	Pale Olive
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 31.8mm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80
SEATPOST	Post Moderne, dropper, 30.9mm with 30mm of suspension S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop
SADDLE	Giant Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Apex AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM X1 Eagle AXS
BRAKES	SRAM Apex AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Apex AXS, left lever dropper switch
CASSETTE	SRAM PG-1230, 12-speed, 11x50
CHAIN	SRAM NX Eagle
CRANKSET	SRAM Apex 1 DUB, 40t S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR X1 Carbon Disc WheelSystem
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, 36t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	Giant CrossCut Grip, 700x45c, tubeless
EXTRAS	Tubeless prepared, 53mm max tyre size in "long" flip chip position, 42mm max tyre size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm max tyre size in "long" flip chip position

Price: \$9,299.00

GEOMETRY

FRAME	XS		S		M		ML		L		XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SH	
Seat Tube Length (mm)	430	450	470	490	510	530					
Seat Tube Angle	74.0° 73.9°	73.5° 73.4°	73.5° 73.4°	73.0° 72.9°	73.0° 72.9°	73.0° 72.9°					
Top Tube Length (mm)	543	553	560	575	585	600					
Head Tube Length (mm)	90	100	115	130	145	160					
Head Tube Angle	70.5° 70.4°	71.0° 70.9°	71.5° 71.4°	72.0° 71.9°	72.0° 71.9°	72.0° 71.9°					
Fork Rake (mm)	50	50	50	50	50	50					
Trail (mm)	80.3 83.7	76.9 80.3	73.5 76.8	70.1 73.4	70.1 73.4	70.1 73.4					
Wheelbase (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041 1051	1051					
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435					
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69	68 69					
Stack (mm)	549	560	576	592	607	622					
Reach (mm)	386	387	389	393	399	410					
Stand Over Height (mm)	720 726	736 743	755 761	772 778	790 796	800					
Stem Length (mm)	50	60	70	80	80	90					
Crank Length (mm)	170	170	172.5	172.5	175	175					
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C					

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.