

REVOLT X ADVANCED PRO 1

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Golden Haze/Cordovan
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	RockShox Rudy Ultimate XPLR, 40mm, Charger Race Day damper12x100mm thru-axle
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SEATPOST	Post Moderne Suspension DSP 30mm suspension, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SADDLE	Giant Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival eTap AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle AXS
BRAKES	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival eTap AXS hydraulic
CASSETTE	SRAM XG-1275, 12-speed, 10x52
CHAIN	SRAM GX Eagle
CRANKSET	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
HUBS	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Laser
TIRES	Maxxis Rambler, 700x45c, tubeless prepared
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Suggested Retail Price (CDN): \$6,499.00

FRAME GEOMETRY

FRAME	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	430	450	450	470	470	490	490	510	510	530	530	550
Seat Tube Angle	74.0°	73.9°	73.5°	73.4°	73.5°	73.4°	73.0°	72.9°	73.0°	72.9°	73.0°	72.9°
Top Tube Length (mm)	543	553	553	560	560	575	575	585	585	600	600	610
Head Tube Length (mm)	90	100	100	115	115	130	130	145	145	160	160	170
Head Tube Angle	70.5°	70.4°	71.0°	70.9°	71.5°	71.4°	72.0°	71.9°	72.0°	71.9°	72.0°	71.9°
Fork Rake (mm)	50	50	50	50	50	50	50	50	50	50	50	50
Trail (mm)	80.3	83.7	76.9	80.3	73.5	76.8	70.1	73.4	70.1	73.4	70.1	73.4
Wheelbase (mm)	1023	1033	1024	1034	1026	1036	1031	1041	1041	1051	1057	1067
Chain Stay Length (mm)	425	435	425	435	425	435	425	435	425	435	425	435
Bottom Bracket Drop (mm)	68	69	68	69	68	69	68	69	68	69	68	69
Stack (mm)	549	560	560	576	576	592	592	607	607	621	621	635
Reach (mm)	386	387	387	389	389	393	393	399	399	410	410	421
Stand Over Height (mm)	720	726	736	743	755	761	772	778	790	796	808	814
Handlebar Width (mm)	440	440	440	460	460	460	460	480	480	480	480	480
Stem Length (mm)	50	60	60	70	70	80	80	80	80	90	90	90
Crank Length (mm)	170	170	170	172.5	172.5	172.5	175	175	175	175	175	175
Wheel Size	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

All prices and specifications are subject to change without notice.