



SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	Cordovan/Copper Coin
CADRU	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FURCA	RockShox Rudy Ultimate XPLR, 40mm, Charger Race Day damper 12x100mm thru-axle
SOC	N/A
COMPONENTE	
GHIDON	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
PIPA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
TIJA SA	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SA	Giant Approach SL
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Rival eTap AXS, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	SRAM GX Eagle AXS
FRANE	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
MANETE FRANA	SRAM Rival eTap AXS hydraulic
PINIOANE	SRAM XG-1275, 12-speed, 10x52
LANT	SRAM GX Eagle
ANGRENAJ	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
BUTUCI	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPITE	Sapim Laser
ANVELOPE	Giant CrossCut Grip 1, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

GEOMETRIE

CADRU	XS	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0° 73,9°	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°
Top Tube Length (mm)	543	553	560	575	585	600
Head Tube Length (mm)	90	100	115	130	145	160
Head Tube Angle	70,5° 70,4°	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	80,3 83,7	76,9 80,3	73,5 76,8	70,1 73,4	70,1 73,4	70,1 73,4
Wheelbase (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041 1051	1051 1061
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69	68 69
Stack (mm)	549	560	576	592	607	621
Reach (mm)	386	387	389	393	399	410
Stand Over Height (mm)	714 720	734 737	750 756	767 773	785 792	803 810
Handlebar Width (mm)	440	440	460	460	480	480
Stem Length (mm)	50	60	70	80	80	80
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700c	700c	700c	700c	700c

Toate specificatiile enumerate se pot schimba fara notificare prealabila.