



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Cordovan/Copper Coin
OKVIR	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
VILICE	RockShox Rudy Ultimate XPLR, 40mm, Charger Race Day damper 12x100mm thru-axle
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
OPORA SEDEŽA	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SEDEŽ	Giant Approach SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM Rival eTap AXS, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle AXS
ZAVORE	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Rival eTap AXS hydraulic
VERIŽNIK	SRAM XG-1275, 12-speed, 10x52
VERIGA	SRAM GX Eagle
GONILKE Z VERIŽNIKI	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
PESTA	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	Sapim Laser
PLAŠČI	Giant CrossCut Grip 1, 700x45c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

GEOMETRIJA

OKVIR	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Dolžina sedežne cevi (mm)	430	450	470	490	510
Kot sedežne cevi	74,0° 73,9°	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°
Top Tube Length (mm)	543	553	560	575	585
Višina glave okvirja (mm)	90	100	115	130	140
Krmilni kot	70,5° 70,4°	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°
Zamik vpetja osi (mm)	50	50	50	50	50
Trail (mm)	80,3 83,7	76,9 80,3	73,5 76,8	70,1 73,4	67,0 70,3
Medosna razdalja (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1036 1046
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69
Oddaljenost zgornje cevi od gonilne osi (mm)	549	560	576	592	608
Doseg (mm)	386	387	389	393	397
Višina zgornje cevi (mm)	714 720	734 737	750 756	767 773	784 790
Širina krmila (mm)	440	440	460	460	460
Dolžina opore krmila (mm)	50	60	70	80	90
Dolžina gonilke (mm)	170	170	172,5	172,5	175
Velikost obročnikov	700C	700c	700c	700c	700c

Vse navedene specifikacije se lahko spremenijo brez obvestila.