

REVOLT X ADVANCED PRO 1



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Clay Gray/Carbon
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	RockShox Rudy Ultimate XPLR, 40mm, Charger Race Day damper 12x100mm thru-axle
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SEATPOST	Post Moderne Suspension DSP 30mm suspension, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SADDLE	Giant Approach SL
DRIVETRAIN	
SHIFTERS	SRAM Rival eTap AXS, 1x12
REAR DERAILLEUR	SRAM GX Eagle AXS
BRAKES	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival eTap AXS hydraulic
CASSETTE	SRAM XG-1275, 12-speed, 10x52
CHAIN	SRAM GX Eagle
CRANKSET	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
HUBS	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Laser
TIRES	Giant Crosscut Grip 1, 700x45C
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0° 73.9°	73.5° 73.4°	73.5° 73.4°	73.0° 72.9°	73.0° 72.9°	73.0° 72.9°
Top Tube Length (mm)	543	553	560	575	585	600
Head Tube Length (mm)	90	100	115	130	145	160
Head Tube Angle	70.5° 70.4°	71.0° 70.9°	71.5° 71.4°	72.0° 71.9°	72.0° 71.9°	72.0° 71.9°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	80.3 83.7	76.9 80.3	73.5 76.8	70.1 73.4	70.1 73.4	70.1 73.4
Wheelbase (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041 1051	1051 1061
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69	68 69	68 69	68 69
Stack (mm)	549	560	576	592	607	622
Reach (mm)	386	387	389	393	399	410
Stand Over Height (mm)	720 726	736 743	755 761	772 778	790 796	808 814
Handlebar Width (mm)	440	440	460	460	480	480
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

All specifications listed are subject to change without notice.