REVOLT X ADVANCED PRO 2



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLOURS	Gloss Misty Forest/.Black Diamond
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
SEATPOST	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SADDLE	Giant Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival 1, 1x11
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Rival 1
BRAKES	SRAM Rival 1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival 1, left lever dropper switch
CASSETTE	SRAM Rival, 11-speed, 11x42
CHAIN	SRAM PC-1130
CRANKSET	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR X1 Carbon Disc WheelSystem, 25.8mm, 25mm inner width
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, 60t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim Laser
TIRES	Giant CrossCut Grip 1, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip positio

Suggested Retail Price (CDN): $5,499.00

FRAME GEOMETRY

FRAME	S	M	ML	L	XL
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Seat Tube Length (mm)	450	470	490	510	530
Seat Tube Angle	73.5° | 73.4°	73.5° | 73.4°	73.0° | 72.9°	73.0° | 72.9°	73.0° | 72.9°
Top Tube Length (mm)	553	560	575	585	600
Head Tube Length (mm)	100	115	130	145	160
Head Tube Angle	71.0° | 70.9°	71.5° | 71.4°	72.0° | 71.9°	72.0° | 71.9°	72.0° | 71.9°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	76.9 | 80.3	73.5 | 76.8	70.1 | 73.4	70.1 | 73.4	70.1 | 73.4
Wheelbase (mm)	1024 | 1034	1026 | 1036	1031 | 1041	1041 | 1051	1057 | 1067
Chain Stay Length (mm)	425 | 435	425 | 435	425 | 435	425 | 435	425 | 435
Bottom Bracket Drop (mm)	68 | 69	68 | 69	68 | 69	68 | 69	68 | 69
Stack (mm)	560	576	592	607	621
Reach (mm)	387	389	393	399	410
Stand Over Height (mm)	734 | 737	750 | 756	767 | 773	785 | 792	803 | 810
Handlebar Width (mm)	440	460	460	480	480
Stem Length (mm)	60	70	80	80	80
Crank Length (mm)	170	172.5	172.5	175	175
Wheel Size	700c	700c	700c	700c	700c

All prices and specifications are subject to change without notice.