

REVOLT X ADVANCED PRO 2

GIANT



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLOURS	Gloss Black/Sea Sparkle
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	RockShox Rudy XPLR, 40mm, cartridge damper12x100mm thru-axle
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL XR D-Fuse, 31.8mm S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SEATPOST	Post Moderne, dropper, 30.9mm with 30mm of suspension S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SADDLE	Giant Approach SL
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	Sram Apex AXS 1X12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Sram X1 AXS Eagle w/ battery protector 1X12
BRAKES	SRAM hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Apex AXS hydraulic, left lever dropper switch
CASSETTE	SRAM PG-1230, 12-speed, 11x50
CHAIN	SRAM CN-EAGL-NX-A1, 12-speed
CRANKSET	SRAM Apex D1 DUB, 40t S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
HUBS	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Laser
TYRES	Maxxis Rambler, 700x45c, tubeless prepared
EXTRAS	Factory tubeless set up, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	700x53mm at long RC
MAX CHAINRING SIZE	SRAM Wide 1x 44T. Shimano GRX 1x 42T

Price: €5,199.00

GEOMETRY

FRAME	M	ML	L
	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	470	490	510
Seat Tube Angle	73.5° 73.4°	73.0° 72.9°	73.0° 72.9°
Top Tube Length (mm)	560	575	585
Head Tube Length (mm)	115	130	145
Head Tube Angle	71.5° 71.4°	72.0° 71.9°	72.0° 71.9°
Fork Rake (mm)	50	50	50
Trail (mm)	73.5 76.8	70.1 73.4	70.1 73.4
Wheelbase (mm)	1026 1036	1031 1041	1041 1051
Chain Stay Length (mm)	425 435	425 435	425 435
Bottom Bracket Drop (mm)	68 69	68 69	68 69
Stack (mm)	576	592	607
Reach (mm)	389	393	399
Stand Over Height (mm)	755 761	772 778	790 796
Handlebar Width (mm)	460	460	480
Stem Length (mm)	70	80	80
Crank Length (mm)	172.5	172.5	175
Wheel Size	700x 42C	700x 42C	700x 42C

All specifications listed are subject to change without notice.