

REVOLT X ADVANCED PRO 2

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Black/Sea Sparkle
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
HORQUILLA	RockShox Rudy XPLR, 40mm, cartridge damper12x100mm thru-axle
AMORTIGUADOR	N/A
COMPONENTES	
MANILLAR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
PUÑOS	Stratus Lite 3.0
POTENCIA	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
TIJA DE SILLÍN	Post Moderne Suspension dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SILLÍN	Giant Approach SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Sram Apex AXS 1X12
DESVIADOR	N/A
CAMBIO TRASERO	Sram X1 AXS Eagle w/ battery protector 1X12
FRENOS	SRAM hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	SRAM Apex AXS hydraulic, left lever dropper switch
CASETTE	SRAM PG-1230, 12-speed, 11x50
CADENA	SRAM CN-EAGL-NX-A1, 12-speed
JGO. PLATOS Y BIELAS	SRAM Apex 1 Wide DUB, 1X40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
BUJES	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
RADIOS	Sapim Laser
CUBIERTAS	Maxxis Rambler, 700x45c, tubeless prepared
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	700x53mm at long RC

Precio: 4.599,00 €

GEOMETRÍA

CUADRO	XS		S		M		ML		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud del tubo del sillín (mm)	430	450	470	490	510	530	550	570	590	610
Ángulo del tubo del sillín	74,0°	73,9°	73,5°	73,4°	73,5°	73,4°	73,0°	72,9°	73,0°	72,9°
Longitud del tubo superior (mm) (mm)	543	553	560	575	585	595	605	615	625	635
Longitud del tubo de dirección (mm) (mm)	90	100	115	130	145	160	175	190	205	220
Ángulo del tubo de dirección	70,5°	70,4°	71,0°	70,9°	71,5°	71,4°	72,0°	71,9°	72,0°	71,9°
Inclinación de la horquilla (mm)	50	50	50	50	50	50	50	50	50	50
Trail (mm) (mm)	80,3	83,7	76,9	80,3	73,5	76,8	70,1	73,4	70,1	73,4
Distancia entre ejes (mm) (mm)	1023	1033	1024	1034	1026	1036	1031	1041	1041	1051
Longitud de la vaina (mm) (mm)	425	435	425	435	425	435	425	435	425	435
Caída del eje de pedalier (mm) (mm)	68	69	68	69	68	69	68	69	68	69
Stack (mm) (mm)	549	560	576	592	607	623	638	654	669	685
Reach (mm) (mm)	386	387	389	393	399	405	411	417	423	429
Altura del suelo al tubo (mm) (mm)	720	726	736	743	755	761	772	778	790	796
Ancho del manillar (mm) (mm)	440	440	460	460	480	480	480	480	480	480
Longitud de la potencia (mm) (mm)	50	60	70	80	80	80	80	80	80	80
Longitud de las bielas (mm) (mm)	170	170	172,5	172,5	175	175	175	175	175	175
Tamaño de ruedas	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.