

REVOLT X ADVANCED PRO 2



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, M/L, L, XL
VÄRIT	Meteor Storm
RUNKO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
HAARUKKA	RockShox Rudy XPLR, 40mm, cartridge damper12x100mm thru-axle
KOMONENTIT	
OHJAUSTANKO	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GRIPIT	Stratus Lite 3.0
OHJAINKANNATIN	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SATULATOLPPA	Post Moderne Suspension dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SATULA	Giant Approach SL
VOIMANSIIRTO	
VAIHDEVIPU	Sram Apex AXS 1X12
TAKAVAIHTAJA	Sram X1 AXS Eagle w/ battery protector 1X12
JARRUT	SRAM hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
JARRUKAHVAT	SRAM Apex AXS hydraulic, left lever dropper switch
RATASPAKKA	SRAM PG-1230, 12-speed, 11x50
KETJUT	SRAM CN-EAGLE-NX-A1, 12-speed
KAMPISARJA	SRAM Apex 1 Wide DUB, 1X40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAVAT	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
PINNAT	Sapim Laser
RENKAAT	Crosscut GRIP 1; 700x45c, tubeless ready
LISÄTIEDOT	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
RAJOITTEET	
MAX RENGASVARA	53mm

Suositus hinta: 4 869,00 €

GEOMETRIA

RUNKO	M	ML	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Satulaputken pituus (mm)	470	490	510	530
Satulaputken kulma	73,5° 73,4°	73,0° 72,9°	73,0° 72,9°	73,0° 72,9°
Vaakaputken pituus (mm)	560	575	585	600
Emäputken pituus (mm)	115	130	145	160
Emäputken kulma	71,5° 71,4°	72,0° 71,9°	72,0° 71,9°	72,0° 71,9°
Haarukan offset (mm)	50	50	50	50
Trail-mitta (mm)	73,5 76,8	70,1 73,4	70,1 73,4	70,1 73,4
Akseliväli (mm)	1026 1036	1031 1041	1041 1051	1057 1067
Takahaarukan alaputken pituus (mm)	425 435	425 435	425 435	425 435
Keskiön pudotus (mm)	68 69	68 69	68 69	68 69
Stack-mitta (mm)	576	592	607	621
Reach-mitta (mm)	389	393	399	410
Standover-mitta (mm)	755 761	772 778	790 796	808 814
Ohjaustangon leveys (mm)	460	460	480	480
Ohjainkannattimen pituus (mm)	70	80	80	90
Kammen pituus (mm)	172,5	172,5	175	175
Rengaskoko	700x 42C	700x 42C	700x 42C	700x 42C

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.