

REVOLT X ADVANCED PRO 2

GIANT



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Meteor Storm
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	RockShox Rudy XPLR, 40mm, cartridge damper12x100mm thru-axle
ONDERDELEN	
STUUR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
ZADELPEN	Post Moderne Suspension dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
ZADEL	Giant Approach SL
AFMONTAGE	
SHIFTERS	Sram Apex AXS 1X12
ACHTERDERAILLEUR	Sram X1 AXS Eagle w/ battery protector 1X12
REMMEN	SRAM hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Apex AXS hydraulic, left lever dropper switch
CASSETTE	SRAM PG-1230, 12-speed, 11x50
AANDRIJVING	SRAM CN-EAGLE-NX-A1, 12-speed
CRANKSET	SRAM Apex 1 Wide DUB, 1X40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAVEN	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim Laser
BANDEN	Crosscut GRIP 1; 700x45c, tubeless ready
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAXIMALE BANDENVRIJHEID	53mm

Adviesprijs: € 4.699,00

GEOMETRIE

FRAME	S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	450		470		490		510		530	
Zitbuis Hoek	73,5°	73,4°	73,5°	73,4°	73,0°	72,9°	73,0°	72,9°	73,0°	72,9°
Frame Lengte (horizontaal) (mm)	553		560		575		585		600	
Balhoofdbuis Lengte (mm)	100		115		130		145		160	
Balhoofdbuis Hoek	71,0°	70,9°	71,5°	71,4°	72,0°	71,9°	72,0°	71,9°	72,0°	71,9°
Vork Sprong (mm)	50		50		50		50		50	
Naloop (mm)	76,9	80,3	73,5	76,8	70,1	73,4	70,1	73,4	70,1	73,4
Wielbasis (mm)	1024	1034	1026	1036	1031	1041	1041	1051	1057	1067
Liggende achtersvork lengte (mm)	425	435	425	435	425	435	425	435	425	435
Bottom Bracket Drop (mm)	68	69	68	69	68	69	68	69	68	69
Stack (mm)	560		576		592		607		621	
Reach (mm)	387		389		393		399		410	
Stand Over Height (mm)	736	743	755	761	772	778	790	796	808	814
Stuur breedte (mm)	440		460		460		480		480	
Stuurpen Lengte (mm)	60		70		80		80		90	
Cranklengte (mm)	170		172,5		172,5		175		175	
Wielmaat	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.