

# REVOLT X ADVANCED PRO 2

GIANT



## TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Gloss Misty Forest/Matte Black Diamond
CADRE	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FOURCHE	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
TIGE DE SELLE	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
SELLE	Giant Approach SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	SRAM Rival 1, 1x11
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM Rival 1
FREINS	SRAM Rival 1 hydraulic, SRAM PacerLine rotors [F]160mm, [R]160mm
LEVIERS DE FREIN	SRAM Rival 1, left lever dropper switch
CASSETTE	SRAM Rival, 11-speed, 11x42
CHAÎNE	SRAM PC-1130
PÉDALIER	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
MOYEUX	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Sapim Laser
PNEUS	Giant CrossCut Grip 1, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 4 600,00 €

## GÉOMÉTRIE

CADRE	XS	S	M	ML	L
	SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT
Longueur de tube de selle (mm)	430	450	470	490	510
Angle de tube de selle	74,0°   73,9°	73,5°   73,4°	73,5°   73,4°	73,0°   72,9°	73,0°   72,9°
Longueur du tube supérieur (mm)	543	553	560	575	585
Longueur du tube de direction (mm)	90	100	115	130	145
Angle du tube de direction	70,5°   70,4°	71,0°   70,9°	71,5°   71,4°	72,0°   71,9°	72,0°   71,9°
Déport de fourche (mm)	50	50	50	50	50
Trail (mm)	80,3   83,7	76,9   80,3	73,5   76,8	70,1   73,4	70,1   73,4
Empattement (mm)	1023   1033	1024   1034	1026   1036	1031   1041	1041   1051
Longueur des bases (mm)	425   435	425   435	425   435	425   435	425   435
Drop du boîtier de pédalier (mm)	68   69	68   69	68   69	68   69	68   69
Stack (mm)	549	560	576	592	607
Reach (mm)	386	387	389	393	399
Hauteur en statique (mm)	714   720	734   737	750   756	767   773	785   792
Largeur de cintre (mm)	440	440	460	460	480
Longueur de potence (mm)	50	60	70	80	80
Longueur des manivelles (mm)	170	170	172,5	172,5	175
Diamètre des roues	700C	700c	700c	700c	700c

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).  
GIANT France se réserve le droit de modifier les spécifications sans préavis.