

REVOLT X ADVANCED PRO 2



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Black/Sea Sparkle
CADRE	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FOURCHE	RockShox Rudy XPLR, 40mm, cartridge damper12x100mm thru-axle
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
TIGE DE SELLE	Post Moderne Suspension dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SELLE	Giant Approach SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Sram Apex AXS 1X12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Sram X1 AXS Eagle w/ battery protector 1X12
FREINS	SRAM hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
LEVIER DE FREIN	SRAM Apex AXS hydraulic, left lever dropper switch
CASSETTE	SRAM PG-1230, 12-speed, 11x50
CHAÎNE	SRAM CN-EAGL-NX-A1, 12-speed
PÉDALIER	SRAM Apex 1 Wide DUB, 1X40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
MOYEUX	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Sapim Laser
PNEUS	Maxxis Rambler, 700x45c, tubeless prepared
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	700x53mm at long RC

Prix Public Conseillé: 4 800,00 €

GÉOMÉTRIE

CADRE	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	430		450		470		490		510		530	
Angle de tube de selle	74,0°	73,9°	73,5°	73,4°	73,5°	73,4°	73,0°	72,9°	73,0°	72,9°	73,0°	
Longueur du tube supérieur (mm)	543		553		560		575		585		600	
Longueur du tube de direction (mm)	90		100		115		130		145		160	
Angle du tube de direction	70,5°	70,4°	71,0°	70,9°	71,5°	71,4°	72,0°	71,9°	72,0°	71,9°	72,0°	
Déport de fourche (mm)	50		50		50		50		50		50	
Trail (mm)	80,3	83,7	76,9	80,3	73,5	76,8	70,1	73,4	70,1	73,4	70,1	
Empattement (mm)	1023	1033	1024	1034	1026	1036	1031	1041	1041	1051	1057	
Longueur des bases (mm)	425	435	425	435	425	435	425	435	425	435	425	435
Drop du boîtier de pédalier (mm)	68	69	68	69	68	69	68	69	68	69	68	69
Stack (mm)	549		560		576		592		607		621	
Reach (mm)	386		387		389		393		399		410	
Hauteur en statique (mm)	720	726	736	743	755	761	772	778	790	796	808	814
Largeur de cintre (mm)	440		440		460		460		480		480	
Longueur de potence (mm)	50		60		70		80		80		90	
Longueur des manivelles (mm)	170		170		172,5		172,5		175		175	
Diamètre des roues	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.