

# REVOLT X ADVANCED PRO 2



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Gloss Misty Forest/Matte Black Diamond
<b>FRAME</b>	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
<b>FORK</b>	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm
<b>SEATPOST</b>	Postmodern, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop
<b>SADDLE</b>	Giant Approach SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Rival 1, 1x11
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM Rival 1
<b>BRAKES</b>	SRAM Rival 1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Rival 1, left lever dropper switch
<b>CASSETTE</b>	SRAM Rival, 11-speed, 11x42
<b>CHAIN</b>	SRAM PC-1130
<b>CRANKSET</b>	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

## WHEELS

<b>RIMS</b>	Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
<b>HUBS</b>	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim Laser
<b>TIRES</b>	Giant CrossCut Grip 1, 700x45c, tubeless
<b>EXTRAS</b>	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT   LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0°   73,9°	73,5°   73,4°	73,5°   73,4°	73,0°   72,9°	73,0°   72,9°	73,0°   72,9°
Top Tube Length (mm)	543	553	560	575	585	600
Head Tube Length (mm)	90	100	115	130	145	160
Head Tube Angle	70,5°   70,4°	71,0°   70,9°	71,5°   71,4°	72,0°   71,9°	72,0°   71,9°	72,0°   71,9°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	80,3   83,7	76,9   80,3	73,5   76,8	70,1   73,4	70,1   73,4	70,1   73,4
Wheelbase (mm)	1023   1033	1024   1034	1026   1036	1031   1041	1041   1051	1051   1061
Chain Stay Length (mm)	425   435	425   435	425   435	425   435	425   435	425   435
Bottom Bracket Drop (mm)	68   69	68   69	68   69	68   69	68   69	68   69
Stack (mm)	549	560	576	592	607	622
Reach (mm)	386	387	389	393	399	410
Stand Over Height (mm)	714   720	734   737	750   756	767   773	785   792	803   810
Handlebar Width (mm)	440	440	460	460	480	480
Stem Length (mm)	50	60	70	80	80	80
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700c	700c	700c	700c	700c

All specifications listed are subject to change without notice.