

REVOLT X ADVANCED PRO 2

GIANT



SPECS

TELAIO	
TAGLIE	XS, S, M, M/L, L, XL
COLORAZIONI	Black/Sea Sparkle
TELAIO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORCELLA	RockShox Rudy XPLR, 40mm, cartridge damper12x100mm thru-axle
AMMORTIZZATORE	N/A
COMPONENTISTICA	
MANUBRIO	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
MANOPOLE	Stratus Lite 3.0
ATTACCO MANUBRIO	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
REGGISSELLA	Post Moderne Suspension dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SELLA	Giant Approach SL
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	Sram Apex AXS 1X12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	Sram X1 AXS Eagle w/ battery protector 1X12
FRENI	SRAM hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
COMANDI FRENO	SRAM Apex AXS hydraulic, left lever dropper switch
PACCO PIGNONI	SRAM PG-1230, 12-speed, 11x50
CATENA	SRAM CN-EAGL-NX-A1, 12-speed
GUARNITURA	SRAM Apex 1 Wide DUB, 1x40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
MOVIMENTO CENTRALE	SRAM DUB, press fit

RUOTE	
CERCHI	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
MOZZI	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
RAGGI	Sapim Laser
COPERTONI	Maxxis Rambler, 700x45c, tubeless prepared
EXTRA	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITI	
SEZIONE MASSIMA SUPPORTATA	700x53mm at long RC

Prezzo: € 4.699

GEOMETRIA

TELAIO	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Lunghezza Tubo Sella (mm)	430		450		470		490		510		530	
Angolo Tubo Sella	74,0°	73,9°	73,5°	73,4°	73,5°	73,4°	73,0°	72,9°	73,0°	72,9°	73,0°	72,9°
Lunghezza Tubo Orizzontale (mm)	543		553		560		575		585		600	
Lunghezza Tubo Sterzo (mm)	90		100		115		130		145		160	
Angolo Sterzo	70,5°	70,4°	71,0°	70,9°	71,5°	71,4°	72,0°	71,9°	72,0°	71,9°	72,0°	71,9°
Rake Forcella (mm)	50		50		50		50		50		50	
Avancorsa (mm)	80,3	83,7	76,9	80,3	73,5	76,8	70,1	73,4	70,1	73,4	70,1	73,4
Interasse (mm)	1023	1033	1024	1034	1026	1036	1031	1041	1041	1051	1057	1067
Lunghezza Carro Posteriore (mm)	425	435	425	435	425	435	425	435	425	435	425	435
Drop Movimento Centrale (mm)	68	69	68	69	68	69	68	69	68	69	68	69
Stack (mm)	549		560		576		592		607		621	
Reach (mm)	386		387		389		393		399		410	
Altezza stand over (mm)	720	726	736	743	755	761	772	778	790	796	808	814
Larghezza Manubrio c/c (mm)	440		440		460		460		480		480	
Lunghezza Attacco Manubrio (mm)	50		60		70		80		80		90	
Lunghezza Pedivella (mm)	170		170		172,5		172,5		175		175	
Dimensione Ruote	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.