

REVOLT X ADVANCED PRO 2



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Meteor Storm
RAM	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
GAFFEL	RockShox Rudy XPLR, 40mm, cartridge damper12x100mm thru-axle
KOMPONENTER	
STYRE	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
SADELSTOLPE	Post Moderne Suspension dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SADEL	Giant Approach SL
DRIVLINJA	
VÄXLAR	Sram Apex AXS 1X12
BAKVÄXEL	Sram X1 AXS Eagle w/ battery protector 1X12
BROMSAR	SRAM hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BROMSSPAKAR	SRAM Apex AXS hydraulic, left lever dropper switch
KASSETT	SRAM PG-1230, 12-speed, 11x50
KEDJA	SRAM CN-EAGL-NX-A1, 12-speed
VEVPARTI	SRAM Apex 1 Wide DUB, 1X40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
NAV	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Sapim Laser
DÄCK	Crosscut GRIP 1; 700x45c, tubeless ready
EXTRAFUNKTIONER	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 55 290,00 kr

GEOMETRY

RAM	S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Längd sadelrör (mm)	450		470		490		510		530	
Vinkel sadelrör	73,5°	73,4°	73,5°	73,4°	73,0°	72,9°	73,0°	72,9°	73,0°	72,9°
Topprörets längd (mm)	553		560		575		585		600	
Styrhuvud Längd (mm)	100		115		130		145		160	
Vinkel styrhuvud	71,0°	70,9°	71,5°	71,4°	72,0°	71,9°	72,0°	71,9°	72,0°	71,9°
Gaffelvinkel (mm)	50		50		50		50		50	
Spår (mm)	76,9	80,3	73,5	76,8	70,1	73,4	70,1	73,4	70,1	73,4
Hjulbas (mm)	1024	1034	1026	1036	1031	1041	1041	1051	1057	1067
Kedjestagslängd (mm)	425	435	425	435	425	435	425	435	425	435
Nedre fäste Drop (mm)	68	69	68	69	68	69	68	69	68	69
Stack (mm)	560		576		592		607		621	
Reach (mm)	387		389		393		399		410	
Stå över höjden (mm)	736	743	755	761	772	778	790	796	808	814
Styrets bredd (mm)	440		460		460		480		480	
Stamlängd (mm)	60		70		80		80		90	
Vevlängd (mm)	170		172,5		172,5		175		175	
Hjulstorlek	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

All specifications listed are subject to change without notice.