

ROAM E+ GTS



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
SENSOR	RideControl One Ant+
ECRÃ	ANT+ Wireless display compatible
BATERIA	EnergyPak 400Wh
QUADRO	
TAMANHOS	S, M, L, XL
CORES	Black
QUADRO	ALUXX Aluminum, Overdrive 1½ - 1½" head tube, integrated KS18 kickstand mount
FORQUILHA	SR Suntour NEX E25 63mm travel
AMORTECEDORES	-
COMPONENTES	
GUIADOR	Giant Connect Riser S:31.8x620mm, M:31.8x680mm, L:31.8x680mm, XL:31.8x680mm
PUNHOS	Giant Connect Ergo
AVANÇO	Giant Contact
ESPIGÃO DE SELIM	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELIM	Giant Sport Comfort
PEDAIS	PP Pedal
TRANSMISSÃO	
MANETES	Shimano Altus
DESVIADOR DIANTEIRO	-
DESVIADOR TRASEIRO	Shimano Alivio, 9-speed
TRAVÕES	Tektro HD-M275, hydraulic disc, 160/180mm
MANÍPULOS DOS TRAVÕES	Tektro HD-M275
CASSETTE	Shimano CS-HG200, 11-36T, 9-speed
CORRENTE	KMC e.9 Sport, e-bike optimized
CONJUNTO PEDALEIRO	Forged Alloy minimal Q-factor, 42T
MOVIMENTO CENTRAL	-

RODAS	
AROS	Giant GX03V, 622x21mm Aluminium
CUBOS	Giant eTracker, [F] 100x9mm QR [R] 135mm QR
RAIOS	Stainless steel
PNEUS	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready W/O Reflex (GU: w/reflex)

Preço: 1 699,00 €

GEOMETRIA

QUADRO	S	M	L	XL
Comprimento do tubo do assento (mm)	435	485	535	585
Ângulo do tubo do assento	74,0°	73,0°	73,0°	73,0°
Comprimento do tubo superior (mm)	570	590	610	630
Comprimento do tubo principal (mm)	130	140	155	170
Ângulo do tubo principal	69,5°	69,5°	69,5°	69,5°
Garfo ancinho (mm)	42	42	42	42
Trilha (mm)	91,3	91,3	91,3	91,3
distância entre eixos (mm)	1112	1121	1142	1163
Comprimento Chain Stay (mm)	455	455	455	455
Suporte inferior (mm)	60	60	60	60
Pilha (mm)	610	619	633	648
Alcançar (mm)	395	400	416	432
Altura do standover (mm)	745	775	808	844
Largura do guidão (mm)	640	680	680	680
Comprimento da haste (mm)	60	70	80	90
Comprimento da Manivela (mm)	170	170	170	170
Tamanho da roda	700C	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.