



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
SENSOR	RideControl One Ant+
PRIKAZ	ANT+ Wireless display compatible
BATERIJA	EnergyPak 400Wh
OKVIR	
VELIČINE	S, M, L
BOJE	Black
OKVIR	ALUXX Aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
VILICA	SR Suntour NEX E25 63mm travel
AMORTIZER	-
KOMPONENTE	
VOLAN	Giant Connect Riser S:31.8x620mm, M:31.8x680mm, L:31.8x680mm
GRIPS	Giant Connect Ergo
LULA VOLANA	Giant Contact
CIJEV SJEDALA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SJEDALO	Giant Sport Comfort
PEDALE	PP Pedal
POGON	
RUČICE MJENJAČA	Shimano Altus
PREDNJI MJENJAČ	-
STRAŽNJI MJENJAČ	Shimano Alivio, 9-speed
KOČNICE	Tektro HD-M275, hydraulic disc, 160/180mm
RUČICE KOČNICA	Tektro HD-M275
KAZETA	Shimano CS-HG200, 11-36T, 9-speed
LANAC	KMC e.9 Sport, e-bike optimized
POGON	Forged Alloy minimal Q-factor, 42T
OSOVINA POGONA (BB)	-

KOTAČI	
OBRUČI	Giant GX03V, 622x21mm Aluminium
NABE	Giant eTracker, [F] 100x9mm QR [R] 135mm QR
ŽBICE	Stainless steel
GUME	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready W/O Reflex (GU: w/reflex)

GEOMETRIJA

OKVIR	S	M	L
Dužina cijevi sjedala (mm)	435	485	535
Kut cijevi sjedala	73,0°	73,0°	73,0°
Dužina gornje cijevi (mm)	570	590	610
Dužina prednje cijevi (mm)	130	140	155
Kut vilice	69,5°	69,5°	69,5°
Zakrivljenost vilice (offset) (mm)	42	42	42
Staza (mm)	91,3	91,3	91,3
Međuosovinski razmak kotača (mm)	1112	1121	1142
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	455	455	455
Položaj osovine pogona (mm)	60	60	60
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	609	618	633
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	383	401	416
Prekoračna visina (mm)	682	676	665
Širina volana (mm)	640	680	680
Dužina lule volana (mm)	60	70	80
Dužina poluge pedale (mm)	170	170	170
Veličina kotača	700C	700C	700C

Sve navedene specifikacije podložne su promjeni bez prethodne najave.